

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54

P802.1Q-REV/D1.5

March 24, 2011

(Incorporates IEEE Std 802.1Q™-2005, IEEE Std 802.1ad™-2005,
IEEE Std 802.1ak™-2007, IEEE Std 802.1ag™-2007,
IEEE Std 802.1ah™-2008, IEEE Std 802-1Q-2005/Cor-1-2008,
IEEE Std 802.1ap™-2008, IEEE Std 802.1Qaw™-2009,
IEEE Std 802.1Qay™-2009, IEEE Std 802.1aj™-2009,
IEEE Std 802.1Qav™-2009, IEEE Std Qau™-2010,
and IEEE Std Qat™-2010)

IEEE P802.1Q-REV/D1.5

Draft Standard for Local and Metropolitan Area Networks—

Media Access Control (MAC) Bridges and Virtual Bridged Local Area Networks

Sponsor

LAN/MAN Standards Committee of the IEEE Computer Society

Prepared by the Interworking Task Group of IEEE 802.1

Abstract: This standard specifies how the MAC Service is supported by Virtual Bridged Local Area Networks, the principles of operation of those networks, and the operation of VLAN-aware Bridges, including management, protocols, and algorithms.

Keywords: Bridged Local Area Networks, local area networks (LANs), MAC Bridges, metropolitan area networks, Multiple Spanning Tree Protocol (MSTP), Rapid Spanning Tree Protocol (RSTP), Virtual Bridged Local Area Networks (virtual LANs)

DRAFT STATUS:

Draft for second Sponsor recirculation ballot, based on the application of the comments on the first Sponsor recirculation ballot.

Copyright © 2011 by the Institute of Electrical and Electronics Engineers, Inc.
345 East 47th Street
New York, NY 10017, USA
All rights reserved.

All rights reserved. This document is an unapproved draft of a proposed IEEE Standard. As such, this document is subject to change. USE AT YOUR OWN RISK! Because this is an unapproved draft, this document must not be utilized for any conformance/compliance purposes. Permission is hereby granted for IEEE Standards Committee participants to reproduce this document for purposes of IEEE standardization activities only. Prior to submitting this document to another standards development organization for standardization activities, permission must first be obtained from the Manager, Standards Licensing and Contracts, IEEE Standards Activities Department. Other entities seeking permission to reproduce this document, in whole or in part, must obtain permission from the Manager, Standards Licensing and Contracts, IEEE Standards Activities Department.

IEEE Standards Department
Copyright and Permissions
445 Hoes Lane, P.O. Box 1331
Piscataway, NJ 08855-1331, USA

1 **IEEE Standards** documents are developed within the IEEE Societies and the Standards Coordinating Committees of the
2 IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus develop-
3 ment process, approved by the American National Standards Institute, which brings together volunteers representing varied
4 viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve with-
5 out compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus devel-
6 opment process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained
7 in its standards.

8 Use of an IEEE Standard is wholly voluntary. The IEEE disclaims liability for any personal injury, property or other dam-
9 age, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting
10 from the publication, use of, or reliance upon this, or any other IEEE Standard document.

11 The IEEE does not warrant or represent the accuracy or content of the material contained herein, and expressly disclaims
12 any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that
13 the use of the material contained herein is free from patent infringement. IEEE Standards documents are supplied “**AS IS.**”
14

15 The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market,
16 or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the
17 time a standard is approved and issued is subject to change brought about through developments in the state of the art and
18 comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revi-
19 sion or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude
20 that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check
21 to determine that they have the latest edition of any IEEE Standard.

22 In publishing and making this document available, the IEEE is not suggesting or rendering professional or other services
23 for, or on behalf of, any person or entity. Nor is the IEEE undertaking to perform any duty owed by any other person or
24 entity to another. Any person utilizing this, and any other IEEE Standards document, should rely upon the advice of a com-
25 petent professional in determining the exercise of reasonable care in any given circumstances.
26

27 Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific
28 applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare
29 appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any
30 interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its
31 societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests
32 except in those cases where the matter has previously received formal consideration.

33 Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with
34 IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate
35 supporting comments. Comments on standards and requests for interpretations should be addressed to:

36 Secretary, IEEE-SA Standards Board
37 445 Hoes Lane
38 P.O. Box 13 31
39 Piscataway, NJ 08855-1331
40 USA
41

42
43 **Note:** Attention is called to the possibility that implementation of this standard may require use of subject mat-
44 ter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or
45 validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying patents
46 for which a license may be required by an IEEE standard or for conducting inquiries into the legal validity or
47 scope of those patents that are brought to its attention.

48 Authorization to photocopy portions of any individual standard for internal or personal use is granted by the Institute of
49 Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To
50 arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive,
51 Danvers, MA 01923 USA; (978) 750-8400. Permission to photocopy portions of any individual standard for educational
52 classroom use can also be obtained through the Copyright Clearance Center.
53
54

Introduction

(This introduction is not part of P802.1Q-REV/D1.5, IEEE Standards for Local and metropolitan area networks—Media Access Control (MAC) Bridges and Virtual Bridged Local Area Networks.)

The MAC Bridge standardization activities that resulted in the development of IEEE Std 802.1D™-1993 introduced the concept of Filtering Services in Bridged Local Area Networks, and mechanisms whereby filtering information in such LANs may be acquired and held in a Filtering Database.

IEEE Std 802.1D™, 1998 Edition, a revision of IEEE Std 802.1D-1993 [B4], extended this concept of Filtering Services to define additional capabilities aimed at

- a) The provision of expedited traffic capabilities, to support the transmission of time-critical information in a LAN environment.
- b) The use of signaled priority information as the basis for identifying expedited classes of traffic.
- c) The provision of filtering services that support the dynamic definition and establishment of Groups in a LAN environment, and the filtering of frames by Bridges such that frames addressed to a particular Group are forwarded only on those LANs that are required to reach members of that Group.
- d) The provision of a Generic Attribute Registration Protocol (GARP) that is used to support the mechanism for providing Group filtering capability and is made available for use in other attribute registration applications.

This standard, first published as IEEE Std 802.1Q-1998, makes use of the concepts and mechanisms of LAN Bridging that were introduced by IEEE Std 802.1D, and it defines additional mechanisms that allow the implementation of Virtual Bridged Local Area Networks. The following mechanisms are described:

- e) Virtual LAN Services.
- f) The operation of the Forwarding Process that is required.
- g) The structure of the Filtering Database that is required.
- h) The nature of the protocols and procedures that are required to provide Virtual LAN services, including the definition of the frame formats used to represent VLAN identification information, and the procedures used to insert and remove VLAN identifiers (VIDs) and the headers in which they are carried.
- i) The ability to support end-to-end signaling of priority information regardless of the intrinsic ability of the underlying MAC protocols to signal priority information.
- j) The management services and operations that are required to configure and administer networks.

The 2005 Revision of the standard incorporated three amendments, IEEE Std 802.1u™-2001, IEEE Std 802.1v™-2001, and IEEE Std 802.1s™-2002, into the text of IEEE Std 802.1Q-1998. These amendments describe enhancements to the standard to allow

- k) Dynamic Group and VLAN registration to be restricted, based on the contents of static filtering entries.
- l) VLAN classification according to link layer protocol type.
- m) Support for VLANs carried over multiple Spanning Tree instances.

This revision of the standard incorporates amendments IEEE Std 802.1ad™-2005, IEEE Std 802.1ak™-2007, IEEE Std 802.1ag™-2007, IEEE Std 802.1ah™-2008, IEEE Std 802-1Q-2005/Cor-1-2008, IEEE Std

1 802.1ap™-2008, IEEE Std 802.1Qaw™-2009, IEEE Std 802.1Qay™-2009, IEEE Std 802.1aj™-2009, and
2 IEEE Std 802.1Qav™-2009 into the text of IEEE Std 802.1Q-2005. These amendments describe
3 enhancements to the standard to allow
4

- 5 n) A service provider to use the architecture and protocols defined in this standard to offer the
6 equivalent of separate LANs, Bridged Local Area Networks, or Virtual Bridged Local Area
7 Networks to a number of customers, while requiring no cooperation between the customers, and
8 minimal cooperation between each customer and the service provider.
- 9 o) The distribution and registration of VLAN membership information using the Multiple VLAN
10 Registration Protocol (MVRP), and the distribution of group membership information using the
11 Multiple MAC Registration Protocol (MMRP), replacing the previous GVRP and GMRP protocols.
- 12 p) Support of Connectivity Fault Management (CFM) capabilities for detecting, isolating, and
13 reporting connectivity faults.
- 14 q) Interconnection of multiple Provider Bridged Networks, allowing a Provider to support up to 2²⁴
15 service instances.
- 16 r) Management of VLAN Bridges via SNMP MIB modules.
- 17 s) Diagnosis of data dependent connectivity faults.
- 18 t) Support for traffic engineering.
- 19 u) The use of Bridging technology as a two-port MAC relay.
- 20 v) Support for the relay of time sensitive data streams.
- 21
- 22

23 This standard contains state-of-the-art material. The area covered by this standard is undergoing evolution.
24 Revisions are anticipated within the next few years to clarify existing material, to correct possible errors, and
25 to incorporate new related material. Information on the current revision state of this and other IEEE 802
26 standards may be obtained from
27

28 Secretary, IEEE-SA Standards Board
29 445 Hoes Lane
30 Piscataway, NJ 08854
31 USA
32
33

34 **Notice to users**

35 **Patents**

36 Attention is called to the possibility that implementation of this standard may require use of subject matter
37 covered by patent rights. By publication of this standard, no position is taken with respect to the existence or
38 validity of any patent rights in connection therewith. A patent holder or patent applicant has filed a statement
39 of assurance that it will grant licenses under these rights without compensation or under reasonable rates,
40 with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants
41 desiring to obtain such licenses. Other Essential Patent Claims may exist for which a statement of assurance
42 has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a
43 license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or
44 determining whether any licensing terms or conditions provided in connection with submission of a Letter of
45 Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this
46 standard are expressly advised that determination of the validity of any patent rights, and the risk of
47 infringement of such rights, is entirely their own responsibility. Further information may be obtained from
48 the IEEE Standards Association.
49
50
51
52
53
54

Laws and regulations

Users of these documents should consult all applicable laws and regulations. Compliance with the provisions of this standard does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

This document is copyrighted by the IEEE. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making this document available for use and adoption by public authorities and private users, the IEEE does not waive any rights in copyright to this document.

Updating of IEEE documents

Users of IEEE standards should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE Standards Association website at <http://ieeexplore.ieee.org/xpl/standards.jsp>, or contact the IEEE at the address listed previously. For more information about the IEEE Standards Association or the IEEE standards development process, visit the IEEE-SA website at <http://standards.ieee.org>.

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/updates/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Interpretations

Current interpretations can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/interp/index.html>.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying patents or patent applications for which a license may be required to implement an IEEE standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention. A patent holder or patent applicant has filed a statement of assurance that it will grant licenses under these rights without compensation or under reasonable rates and nondiscriminatory, reasonable terms and conditions to applicants desiring to obtain such licenses. The IEEE makes no representation as to the reasonableness of

1 rates, terms, and conditions of the license agreements offered by patent holders or patent applicants. Further
2 information may be obtained from the IEEE Standards Department.
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54

Participants

The following is a list of participants in the Interworking activities of the IEEE 802.1 Working Group at the time of publication of the 2005 Revision.

Tony Jeffrey, *Chair and Editor*
Paul Congdon, *Vice Chair*
Mick Seaman, *Chair, Interworking Task Group*

Mike Borza	Romain Insler	Dan Romascanu
Paul Bottorff	Ran Ish-Shalom	Jessy V. Rouyer
Jim Burns	Michael Johas Teener	Ali Sajassi
Dirceu Cavendish	Hal Keen	Panagiotis Saltsidis
Arjan de Heer	Yongbum Kim	Sam Sambasivan
Russell Dietz	Loren Larsen	John Sauert
Linda Dunbar	Yannick Le Goff	Koichiro Seto
Anush Elangovan	David Martin	Curtis Simonson
Hesham Elbakoury	John Messenger	Bob Sultan
David Elie-Dit-Cosaque	Dinesh Mohan	Muneyoshi Suzuki
Don Fedyk	Bob Moskowitz	Yoshihiro Suzuki
Norm Finn	Don O'Connor	Francois Tallet
David Frattura	Karen O'Donoghue	John Viega
Anoop Ghanwani	Glenn Parsons	Dennis Volpano
Ken Grewal	Ken Patton	Manoj Wadekar
Steve Haddock	Ray Qiu	Ludwig Winkel
Takashi Hasegawa	Karen Randall	Michael D. Wright
	Allyn Romanow	

The following members of the individual balloting committee voted on the 2005 Revision of this standard. Balloters may have voted for approval, disapproval, or abstention.

Brandon Barry	Neil Jarvis	Jessy V. Rouyer
Les Bell	Tony Jeffrey	Ali Sajassi
Mike Borza	Hal Keen	Dolors Sala
Paul Bottorff	Yongbum Kim	Sam Sambasivan
Jim Burns	Shobhan Lakkapragada	John Sauer
Dirceu Cavendish	Bill Lane	Mick Seaman
Paul Congdon	Loren Larson	Koichiro Seto
Sharam Davari	Yannick Le Goff	Muneyoshi Suzuki
Arjan de Heer	Marcus Leech	Jonathan Thatcher
Craig Easley	John Messenger	Geoff Thompson
Anush Elangovan	Dinesh Mohan	Michel Thorsen
Helsham Elbakoury	Bob Moskowitz	Jonathan R. Thatcher
David Elie-Dit-Cosaque	Don O'Connor	John Viega
Norm Finn	Don Pannell	Preeti Vinayakray-Jani
David Farttura	Glenn Parsons	John Vollbrecht
Gerard Goubert	Karen Randall	Dennis Valpano
Stephen Haddock	Allyn Romanow	Karl Weber
Ran Ish-Shalom	Dan Romascanu	Ludwig Winkel
Atsushi Iwata		Michael D. Wright

1 When the IEEE-SA Standards Board approved the 2005 Revision of this standard on 7 December 2005, it
2 had the following membership:

3
4 **Steve M. Mills, *Chair***
5 **Richard H. Hulett, *Vice Chair***
6 **Don Wright, *Past Chair***
7 **Judith Gorman, *Secretary***

8 Mark D. Bowman
9 Dennis B. Brophy
10 Joseph Bruder
11 Richard Cox
12 Bob Davis
13 Julian Forster*
14 Joanna N. Guenin
15 Mark S. Halpin
16 Raymond Hapeman

William B. Hopf
Lowell G. Johnson
Herman Koch
Joseph L. Koepfinger*
David J. Law
Daleep C. Mohla
Paul Nikolich

T. W. Olsen
Glenn Parsons
Ronald C. Petersen
Gary S. Robinson
Frank Stone
Malcolm V. Thaden
Richard L. Townsend
Joe D. Watson
Howard L. Wolfman

17
18
19 *Member Emeritus

20
21 Also included are the following nonvoting IEEE-SA Standards Board liaisons:

22
23
24 Satish K. Aggarwal, *NRC Representative*
25 Richard DeBlasio, *DOE Representative*
26 Alan H. Cookson, *NIST Representative*

27
28 Jennie M. Steinhagen
29 *IEEE Standards Project Editor*

Historical participants

Since the initial publication, many IEEE standards have added functionality or provided updates to material included in this standard. The following is a historical list of participants who have dedicated their valuable time, energy, and knowledge to the creation of this material:

IEEE 802.1Q Standard	Date approved by IEEE	Officers at the time of Working Group Letter Ballot
IEEE Std 802.1Q-1998	8 December 1998	William P. Lidinsky , <i>Chair</i> Mick Seaman , <i>Chair, Interworking Task Group</i> Tony Jeffree , <i>Coordinating Editor</i> Anil Rijasinghani, Richard Hausmann, Michele Wright, Paul Langille, P. J. Singh , <i>Editorial Team</i>
IEEE Std 802.1u-2001	17 March 2001	Tony Jeffree , <i>Chair</i> Neil Jarvis , <i>Vice Chair</i> Mick Seaman , <i>Chair, Interworking Task Group</i>
IEEE Std 802.1v-2001	17 March 2001	Tony Jeffree , <i>Chair</i> Neil Jarvis , <i>Vice Chair</i> Mick Seaman , <i>Chair, Interworking Task Group</i> David Delany , <i>Editor</i> Andrew Smith , <i>Editor</i>
IEEE Std 802.1s-2002	11 December 2002	Tony Jeffree , <i>Chair</i> Neil Jarvis , <i>Vice Chair</i> Mick Seaman , <i>Chair, Interworking Task Group</i> Norman W. Finn , <i>Editor</i>
IEEE Std 802.1ad-2005	28 March 2005	Tony Jeffree , <i>Chair</i> Paul Congdon , <i>Vice Chair</i> Mick Seaman , <i>Chair, Interworking Task Group</i> Stephen R. Haddock , <i>Editor</i>
IEEE Std 802.1Q-2005	7 December 2005	Tony Jeffree , <i>Chair and Editor</i> Paul Congdon , <i>Vice Chair</i> Mick Seaman , <i>Chair, Interworking Task Group</i>
IEEE Std 802.1ak-2007	22 March 2007	Tony Jeffree , <i>Chair and Editor</i> Paul Congdon , <i>Vice Chair</i> Mick Seaman , <i>Chair, Interworking Task Group</i>

IEEE 802.1Q Standard	Date approved by IEEE	Officers at the time of Working Group Letter Ballot
IEEE Std 802.1ag-2007	27 September 2007	Tony Jeffree , <i>Chair</i> Paul Congdon , <i>Vice Chair</i> Stephen R. Haddock , <i>Chair, Interworking Task Group</i> Norman W. Finn , <i>Editor-in-Chief</i> David V. Elie-Dit-Cosaque, Dinesh Mohan, Oscar Rodriguez, and Ali Sajassi , <i>Assistant Editors</i>
IEEE Std 802.1ah-2008	12 June 2008	Tony Jeffree , <i>Chair</i> Paul Congdon , <i>Vice Chair</i> Stephen R. Haddock , <i>Chair, Interworking Task Group</i> Paul Bottorff, Stephen Haddock, and Muneyoshi Suzuki , <i>Editors</i>
IEEE Std 802.1Q-2005/ Cor-1-2008	26 September 2008	Tony Jeffree , <i>Chair and Editor</i> Paul Congdon , <i>Vice Chair</i> Stephen R. Haddock , <i>Chair, Interworking Task Group</i>
IEEE Std 802.1ap-2008	10 December 2008	Tony Jeffree , <i>Chair</i> Paul Congdon , <i>Vice Chair</i> Stephen R. Haddock , <i>Chair, Interworking Task Group</i> Glenn Parsons , <i>Editor</i> David Levi , <i>Assistant Editor</i>
IEEE Std 802.1Qaw-2009	17 June 2009	Tony Jeffree , <i>Chair</i> Paul Congdon , <i>Vice Chair</i> Stephen R. Haddock , <i>Chair, Interworking Task Group</i> Linda Dunbar , <i>Editor</i>
IEEE Std 802.1Qay:2009	17 June 2009	Tony Jeffree , <i>Chair</i> Paul Congdon , <i>Vice Chair</i> Stephen R. Haddock , <i>Chair, Interworking Task Group</i> Panagiotis Saltsidis , <i>Editor</i>
IEEE Std 802.1aj:2009	9 December 2009	Tony Jeffree , <i>Chair</i> Paul Congdon , <i>Vice Chair</i> Stephen R. Haddock , <i>Chair, Interworking Task Group</i> John Messenger , <i>Editor</i> Brian Hassink , <i>MIB Editor</i>

1	IEEE 802.1Q Standard	Date approved by IEEE	Officers at the time of Working Group Letter Ballot
2			
3			
4			
5	IEEE Std 802.1Qav-2009	9 November 2009	Tony Jeffree , <i>Chair and Editor</i>
6			Paul Congdon , <i>Vice Chair</i>
7			Michael Johas Teener , <i>Chair; Audio</i>
8			<i>Video Bridging Task Group</i>
9			
10			
11	IEEE Std 802.1Qau-2010	25 March 2010	Tony Jeffree , <i>Chair</i>
12			Paul Congdon , <i>Vice Chair</i>
13			Patricia Thaler , <i>Chair; Data Center</i>
14			<i>Bridging Task Group</i>
15			Norman W. Finn , <i>Editor</i>
16			
17			
18	IEEE Std 802.1Qat-2010	30 September 2010	Tony Jeffree , <i>Chair</i>
19			Paul Congdon , <i>Vice Chair</i>
20			Michael Johas Teener , <i>Chair; Audio</i>
21			<i>Video Bridging Task Group</i>
22			Craig Gunther , <i>Editor</i>
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			

1	Osama Aboul-Magd	Claudio Desanti	Romain Insler
2	Steve Adams	Jeffrey Dietz	Ran Ish-Shalom
3	Stephen Ades	Russell Dietz	Vipin K. Jain
4	Zehavit Alon	Zhemin Ding	Tony Jeffree
5	Ken Alonge	Kurt Dobbins	Paul Hongkyu Jeong
6	Ting Ao	Linda Dunbar	Michael Johas Teener
7	Siamack Ayandeh	Craig Easley	Pankaj Jha
8	Floyd Backes	Donald Eastlake, III	Shyam Kaluve
9	John Bartlett	Peter Ecclesine	Abhay Karandikar
10	Alexei Beliaev	J. J. Ekstrom	Allen Kasey
11	Les Bell	Anush Elangovan	Prakash Kashyap
12	Avner Ben-Dor	Hesham M. Elbakoury	Toyayuki Kato
13	Michael Berger	David Elie-Dit-Cosaque	Hal Keen
14	Caitlin Bestler	Janos Farkas	Daniel Kelley
15	Jan Bialkowski	Donald W. Fedyk	Kevin Ketchum
16	James S. Binder	Felix Feifei Feng	Keti Kilcrease
17	Rob Boatright	Norman Finn	Doyeon Kim
18	Jean-Michel Bonnamy	Yishai Fraenkel	Yongbum Kim
19	Mike Borza	Paul Frantz	Keith Klamm
20	Paul Bottorff	David Frattura	Philippe Klein
21	David Brady	Robert Frazier	Bruce Kling
22	Rudolf Brandner	Lars Henrik Frederiksen	Walter Knitl
23	Martin Brewer	John Fuller	Mike Ko
24	Bill Bunch	Geoffrey Garner	Raghu Kondapalli
25	Jim Burns	Anoop Ghanwani	Michael Krause
26	Bob Cardinal	Franz Goetz	Dan Krent
27	Craig W. Carlson	Eric Gray	Vinod Kumar
28	Paul Carroll	Karanvir Grewal	Paul Kummer
29	Jeffrey Catlin	John Grinham	Bruce Kwan
30	Dennis Cave	Craig Gunther	Paul Lachapelle
31	Dirceu Cavendish	Mitch Gusat	Kari Laihonon
32	Alan Chambers	Stephen Haddock	Ashvin Lakshmikantha
33	Steve Chan	Sharam Hakimi	Bill Lane
34	David W. Chang	John Hart	Loren Larsen
35	Frank Chao	Scott Harvell	Yannick Le Goff
36	Ken Chapman	Takashi Hasegawa	John Lemon
37	Weiyang Cheng	Brian Hassink	Michael Lerer
38	Rao Cherukuri	Wayne Hathaway	Johann Lindmeyr
39	Taesik Cheung	Brian Hausauer	Marina Lipshteyn
40	Hon Wah Chin	Vic Hayes	Gary Littleton
41	Jin-Seek Choi	Asif Hazarika	Yuanqui Luo
42	Chi Chong	David Head	Robert D. Love
43	Chris Christ	Gaby Hecht	Andy Luque
44	Marc Cochran	Deepak Hegde	Gael Mace
45	Paul Congdon	Ariel Hendel	Ben Mack-Crane
46	Glenn Connery	John Hickey	David Martin
47	Alex Conta	David Hollender	Peter Martini
48	Diego Crupnicoff	Steve Horowitz	Riccardo Martinotti
49	David Cullerot	Bob Hott	Marco Mascitto
50	Uri Cummings	Michelle Hsiung	Keith McCloghrie
51	Ted Davies	Charles Hudson	Alan McGuire
52	Andy Davis	Rita Hunt	
53	Arjan de Heer	David Husak	
54	Prakash Desai	Altah Hussain	

1			
2	James McIntosh	James Richmond	Attila Takacs
3	Martin McNealis	Robert Roden	Francois Tallet
4	Menucher Menuchery	Guenter Roeck	Robin Tasker
5	Milan Merhar	John J. Roese	John Terry
6	John Messenger	Josef Roese	Patricia A. Thaler
7	Colin Mick	Derek J. Rohde	Geoff Thompson
8	Amol Mitra	Allyn Romanow	Oliver Thorp
9	Dinesh Mohan	Dan Romascanu	Michel Thorsen
10	Gabriel Montenegro	Moran Roth	Fouad Tobagi
11	Matthew Mora	Jessy V. Rouyer	Naoki Tsukutari
12	John Morris	Doug Ruby	Fred Tuck
13	Bob Moskowitz	Eric Ryu	Paul Unbehagen
14	Eric Multanen	Jonathan Sadler	Dhadesugoor Vaman
15	Yaron Nachman	Ali Sajassi	Steve Van Seters
16	Krishna Narayanaswamy	Joseph Salowey	Dono van-Mierop
17	Lawrence Ng	Panagiotis Saltsidis	John Viega
18	Henry Ngai	Sam Sambasivan	Maarten Vissers
19	Paul Nikolich	Ray Samora	Dennis Volpano
20	Kevin Nolish	Satish Sathe	Manoj Wadekar
21	Don O'Connor	John M. Sauer	Yuchua Wei
22	Karen O'Donoghue	Ayman Sayed	John Wakerly
23	Eugene O'Neil	Ted Schroeder	Peter Wang
24	Satoshi Obara	Benjamin Schultz	Philip Wang
25	Hiroshi Ohta	Michael J. Seaman	Y. C. Wang
26	David Olsen	Rich Seifert	Yan Wang
27	Toshio Ooka	Lee Sendelbach	Trevor Warwick
28	Jörg Ottensmeyer	Koichiro Seto	Bob Watson
29	Shlomo Ovadia	Himanshu Shah	Karl Weber
30	Vijoy Pandey	Rakesh Sharma	Brian Weis
31	Don Pannell	Ravi Shenoy	Alan Weissberger
32	Luc Pariseau	K. Karl Shimada	Glenn Wenig
33	Glenn W. Parsons	Fred Shu	Martin White
34	Ken Patton	Taeshi Shimizu	Bert Wijnen
35	Joe Pelissier	Phil Simmons	Keith Willette
36	Yonadav Perry	Curtis Simonson	Robert Williams
37	David Peterson	Rosemary V. Slager	Ludwig Winkel
38	John Pickens	Alexander Smith	Robert Winter
39	Hayim Porat	Michel Soerensen	Michael Witkowski
40	Gideon Prat	Stuart Soloway	Edward Wong
41	Kirk Preiss	Nurit Sprecher	Michael D. Wright
42	Max Pritikin	Kevin B. Stanton	Chien-Hsien Wu
43	Ray Qiu	Larry Stefani	Ken Young
44	Ananda Rajagopal	Sundar Subramaniam	Allen Yu
45	Steve Ramberg	Robert Sultan	Wayne Zakowski
46	Karen Randall	Muneyoshi Suzuki	Glen Zorn
47	Shlomo Reches	Yoshihiro Suzuki	
48	Frank Reichstein	George Swallow	
49	Dick Reohr	Richard Sweatt	
50			
51			
52			
53			
54			

Contents

1		
2		
3		
4	1. Overview.....	1
5		
6	1.1 Scope.....	2
7	1.2 Purpose.....	2
8	1.3 Introduction.....	2
9	1.4 VLAN aims and benefits	6
10		
11	2. Normative references	8
12		
13	3. Definitions	11
14		
15	4. Abbreviations.....	26
16		
17		
18	5. Conformance.....	30
19		
20	5.1 Requirements terminology.....	30
21	5.2 Conformant components and equipment	30
22	5.3 Protocol Implementation Conformance Statement (PICS).....	31
23	5.4 VLAN-aware Bridge component requirements	31
24	5.4.1 VLAN-aware Bridge component options	32
25	5.4.2 Multiple VLAN Registration Protocol (MVRP) requirements.....	35
26	5.4.4 Multiple Stream Registration Protocol (MSRP) requirements	36
27	5.5 C-VLAN component conformance.....	37
28	5.5.1 C-VLAN component options.....	37
29	5.6 S-VLAN component conformance	37
30	5.6.1 S-VLAN component options	38
31	5.6.2 S-VLAN component requirements for PBB-TE.....	38
32	5.7 I-component conformance	38
33	5.7.1 I-component options	38
34	5.8 B-component conformance.....	39
35	5.8.1 B-component options	39
36	5.8.2 B-component requirements for PBB-TE	39
37	5.9 VLAN Bridge conformance.....	40
38	5.9.1 VLAN Bridge options.....	40
39	5.10 Provider Bridge conformance	40
40	5.10.1 S-VLAN Bridge conformance	40
41	5.10.2 Provider Edge Bridge conformance.....	40
42	5.11 Backbone Edge Bridge conformance	41
43	5.11.1 Backbone Edge Bridge requirements for PBB-TE	41
44	5.12 VLAN-unaware Bridge component requirements	41
45	5.13 TPMR component conformance	41
46	5.13.1 TPMR component options	42
47	5.14 TPMR conformance.....	42
48	5.14.1 TPMR options.....	42
49	5.15 T-component conformance	42
50	5.15.1 T-component options	43
51	5.16 End station requirements for MMRP, MVRP, and MSRP	43
52	5.16.1 MMRP requirements and options	43
53	5.16.2 MVRP requirements and options.....	43
54		

1	5.16.3	MSRP requirements and options	44
2	5.17	VLAN-aware end station requirements for Connectivity Fault Management.....	44
3	5.18	End station requirements—forwarding and queuing for time-sensitive streams.....	45
4	5.19	End station requirements for congestion notification	45
5	5.20	MAC-specific bridging methods	46
6			
7	6.	Support of the MAC Service	47
8			
9	6.1	Basic architectural concepts and terms	48
10	6.1.1	Protocol entities, peers, layers, services, and clients	48
11	6.1.2	Service interface primitives, parameters, and frames	48
12	6.1.3	Layer management interfaces	49
13	6.1.4	Service access points, interface stacks, and ports	49
14	6.1.5	MAC method independent protocols and shims	50
15	6.1.6	MAC Service clients	50
16	6.1.7	Stations and systems	51
17	6.1.8	Connectionless connectivity	51
18	6.2	Provision of the MAC service	51
19	6.2.1	Point-to-point, multipoint-to-multipoint, and rooted-multipoint connectivity	52
20	6.3	Support of the MAC service	52
21	6.4	Preservation of the MAC service	53
22	6.5	Quality of service maintenance.....	53
23	6.5.1	Service availability	53
24	6.5.2	Frame loss	54
25	6.5.3	Frame misordering	55
26	6.5.4	Frame duplication	55
27	6.5.5	Transit delay	55
28	6.5.6	Frame lifetime	56
29	6.5.7	Undetected frame error rate	56
30	6.5.8	Maximum Service Data Unit Size	56
31	6.5.9	Priority	56
32	6.5.10	Throughput.....	57
33	6.6	Internal Sublayer Service.....	58
34	6.6.1	Service primitives and parameters	58
35	6.6.2	Status parameters	60
36	6.6.3	Point-to-point parameters	60
37	6.6.4	Stream Reservation Protocol (SRP) Domain status parameters	60
38	6.7	Support of the Internal Sublayer Service by specific MAC procedures	61
39	6.7.1	Support of the Internal Sublayer Service by IEEE Std 802.3 (CSMA/CD)	61
40	6.7.2	Support by IEEE Std 802.11 (Wireless LAN).....	63
41	6.7.3	Support by IEEE Std 802.17TM (RPR).....	64
42	6.7.4	Support by IEEE Std 802.20 Mobile Broadband Wireless Access Method (MBWA)	65
43	6.8	Enhanced Internal Sublayer Service	67
44	6.8.1	Service primitives	67
45	6.8.2	Status parameters	68
46	6.8.3	Point-to-point parameters	68
47	6.9	Support of the EISS	68
48	6.9.1	Data indications	69
49	6.9.2	Data requests.....	70
50	6.9.3	Priority Code Point encoding.....	70
51	6.9.4	Regenerating priority	72
52	6.10	Support of the ISS/EISS by Provider Instance Ports	73
53	6.10.1	Data indications	75
54			

1	6.10.2	Data requests.....	76
2	6.10.3	Priority Code Point encoding.....	77
3	6.11	Support of the EISS by Customer Backbone Ports.....	77
4	6.11.1	Data indications.....	78
5	6.11.2	Data requests.....	79
6	6.11.3	Priority Code Point decoding.....	80
7	6.11.4	Regenerating priority.....	80
8	6.12	Protocol VLAN classification.....	80
9	6.12.1	Protocol Templates.....	82
10	6.12.2	Protocol Group Identifiers.....	82
11	6.12.3	Protocol Group Database.....	83
12	6.13	Support of the ISS for attachment to a Provider Bridged Network.....	83
13	6.13.1	Data requests.....	84
14	6.13.2	Data indications.....	85
15	6.14	Support of the ISS within a system.....	85
16	6.15	Support of the ISS by additional technologies.....	86
17	6.16	Filtering services in Bridged Local Area Networks.....	86
18	6.16.1	Purpose(s) of filtering service provision.....	86
19	6.16.2	Goals of filtering service provision.....	87
20	6.16.3	Users of filtering services.....	87
21	6.16.4	Basis of service.....	87
22	6.16.5	Categories of service.....	87
23	6.16.6	Service configuration.....	88
24	6.16.7	Service definition for Extended Filtering Services.....	88
25	6.17	EISS Multiplex Entity.....	89
26	6.18	Backbone Service Instance Multiplex Entity.....	90
27	6.18.1	Demultiplexing direction.....	92
28	6.18.2	Multiplexing direction.....	93
29	6.18.3	Priority Code Point encoding.....	93
30	6.18.4	Status parameters.....	94
31	6.19	TESI Multiplex Entity.....	94
32	6.20	Support of the ISS with signaled priority.....	95
33	6.20.1	Data indications.....	96
34	6.20.2	Data requests.....	96
35			
36	7.	Principles of network operation.....	97
37			
38	7.1	Network overview.....	97
39	7.2	Use of VLANs.....	98
40	7.3	VLAN topology.....	99
41	7.4	Locating end stations.....	99
42	7.5	Ingress, forwarding, and egress rules.....	101
43			
44	8.	Principles of bridge operation.....	103
45			
46	8.1	Bridge operation.....	103
47			
48	8.1.1	Relay.....	103
49	8.1.2	Filtering and relaying information.....	104
50	8.1.3	Duplicate frame prevention.....	104
51	8.1.4	Traffic segregation.....	104
52	8.1.5	Traffic reduction.....	105
53	8.1.6	Traffic expediting.....	105
54	8.1.7	Conversion of frame formats.....	105

1	8.2	Bridge architecture.....	106
2	8.3	Model of operation.....	107
3	8.4	Active topologies, learning, and forwarding	110
4	8.5	Bridge Port Transmit and Receive.....	111
5	8.5.1	Bridge Port connectivity	111
6	8.5.2	TPMR Port connectivity	112
7	8.5.3	Support of Higher Layer Entities.....	113
8	8.6	The Forwarding Process	113
9	8.6.1	Active topology enforcement.....	114
10	8.6.2	Ingress filtering.....	115
11	8.6.3	Frame filtering	115
12	8.6.4	Egress.....	117
13	8.6.5	Flow classification and metering	117
14	8.6.6	Queuing frames.....	118
15	8.6.7	Queue management.....	118
16	8.6.8	Transmission selection.....	120
17	8.7	The Learning Process.....	122
18	8.7.1	Default filtering utility criteria.....	122
19	8.7.2	Enhanced filtering utility criteria	122
20	8.8	The Filtering Database.....	122
21	8.8.1	Static Filtering Entries	125
22	8.8.2	Static VLAN Registration Entries	126
23	8.8.3	Dynamic Filtering Entries.....	127
24	8.8.4	MAC Address Registration Entries	128
25	8.8.5	Dynamic VLAN Registration Entries.....	128
26	8.8.6	Default Group filtering behavior	128
27	8.8.7	Dynamic Reservation Entries	130
28	8.8.8	Allocation of VIDs to FIDs	130
29	8.8.9	Querying the Filtering Database	133
30	8.8.10	Determination of the member set for a VID	136
31	8.8.11	Permanent Database.....	137
32	8.8.12	Connection_Identifier	137
33	8.9	MST and ESP configuration information	137
34	8.9.1	MST Configuration Table.....	138
35	8.9.2	MST configuration identification	138
36	8.9.3	FID to MSTI Allocation Table	138
37	8.10	Spanning Tree Protocol Entity.....	138
38	8.11	MRP Entities.....	139
39	8.12	Bridge Management Entity.....	139
40	8.13	Addressing	139
41	8.13.1	End stations.....	139
42	8.13.2	Bridge Ports	139
43	8.13.3	Use of LLC by Spanning Tree Protocol Entities	140
44	8.13.4	Reserved MAC Addresses	140
45	8.13.5	Group MAC Addresses for spanning tree protocols.....	140
46	8.13.6	Group MAC Addresses for MRP Applications	141
47	8.13.7	Bridge Management Entities	141
48	8.13.8	Unique identification of a Bridge	142
49	8.13.9	Points of attachment and connectivity for Higher Layer Entities.....	142
50	8.13.10	VLAN attachment and connectivity for Higher Layer Entities	145
51	8.13.11	Connectivity Fault Management entities	146
52			
53	9.	Tagged frame format	148
54			

1	9.1	Purpose of tagging	148
2	9.2	Representation and encoding of tag fields	148
3	9.3	Tag format.....	149
4	9.4	Tag Protocol Identifier (TPID) formats	149
5	9.5	Tag Protocol Identification	149
6	9.6	VLAN Tag Control Information.....	150
7	9.7	Backbone Service Instance Tag Control Information.....	151
8			
9			
10		10. Multiple Registration Protocol (MRP) and Multiple MAC Registration Protocol	
11		(MMRP).....	153
12			
13	10.1	MRP overview	153
14	10.2	MRP architecture	155
15	10.3	MRP Attribute Propagation (MAP).....	157
16	10.3.1	MAP Context	158
17	10.4	Requirements to be met by MRP	159
18	10.5	Requirements for interoperability between MRP Participants	159
19	10.6	Protocol operation.....	161
20	10.7	Protocol specification	165
21	10.7.1	Notational conventions and abbreviations	165
22	10.7.2	Registrar Administrative Controls	167
23	10.7.3	Applicant Administrative Controls	168
24	10.7.4	Protocol timers.....	168
25	10.7.5	Protocol event definitions	168
26	10.7.6	Protocol Action definitions.....	171
27	10.7.7	Applicant state machine.....	173
28	10.7.8	Registrar state machine	175
29	10.7.9	LeaveAll state machine.....	175
30	10.7.10	PeriodicTransmission state machine.....	175
31	10.7.11	Timer values	176
32	10.7.12	Operational reporting and statistics	177
33	10.7.13	Interoperability considerations	177
34	10.8	Structure and encoding of MRP Protocol Data Units.....	178
35	10.8.1	Structure.....	178
36	10.8.2	Encoding of MRPDU parameters	179
37	10.8.3	Packing and parsing MRPDUs	183
38	10.9	Multiple MAC Registration Protocol (MMRP)—Purpose	184
39	10.10	Model of operation.....	185
40	10.10.1	Propagation of Group Membership information	186
41	10.10.2	Propagation of Group service requirement information	187
42	10.10.3	Source pruning.....	187
43	10.10.4	Use of Group service requirement registration by end stations.....	188
44	10.11	Default Group filtering behavior and MMRP propagation	188
45	10.12	Definition of the MMRP application	189
46	10.12.1	Definition of MRP protocol elements.....	189
47	10.12.2	Provision and support of Extended Filtering Services.....	192
48	10.12.3	Use of “new” declaration capability	193
49	10.12.4	Attribute value support requirements	193
50			
51		11. VLAN topology management.....	195
52			
53	11.1	Static and dynamic VLAN configuration	195
54	11.2	Multiple VLAN Registration Protocol	196

1	11.2.1	MVRP overview	196
2	11.2.2	VLAN registration service definition	198
3	11.2.3	Definition of the MVRP application.....	199
4	11.2.4	VID translation table.....	201
5	11.2.5	Use of “new” declaration capability	201
6	11.2.6	Attribute value support requirements	202
7			
8	12.	Bridge management	203
9			
10	12.1	Management functions.....	203
11	12.1.1	Configuration Management	203
12	12.1.2	Fault Management	204
13	12.1.3	Performance Management	204
14	12.1.4	Security Management	204
15	12.1.5	Accounting Management.....	204
16	12.2	VLAN-aware bridge objects	204
17	12.3	Data types	205
18	12.4	Bridge Management Entity	206
19	12.4.1	Bridge Configuration	206
20	12.4.2	Port configuration	208
21	12.5	MAC entities.....	209
22	12.6	Forwarding process.....	209
23	12.6.1	The Port Counters	209
24	12.6.2	Priority handling	210
25	12.6.3	Traffic Class Table	218
26	12.7	Filtering Database	218
27	12.7.1	The Filtering Database.....	219
28	12.7.2	A Static Filtering Entry	220
29	12.7.3	A Dynamic Filtering Entry	220
30	12.7.4	A MAC Address Registration Entry	220
31	12.7.5	A VLAN Registration Entry	220
32	12.7.6	Permanent Database.....	221
33	12.7.7	General Filtering Database operations.....	221
34	12.8	Bridge Protocol Entity	223
35	12.8.1	The Protocol Entity	223
36	12.8.2	Bridge Port.....	227
37	12.9	MRP Entities.....	230
38	12.9.1	The MRP Timer object	231
39	12.9.2	The MRP Attribute Type object.....	231
40	12.9.3	Periodic state machine objects.....	232
41	12.10	Bridge VLAN managed objects.....	233
42	12.10.1	Bridge VLAN Configuration managed object.....	233
43	12.10.2	VLAN Configuration managed object.....	237
44	12.10.3	The VLAN Learning Constraints managed object	238
45	12.11	MMRP entities.....	244
46	12.11.1	MMRP Configuration managed object.....	244
47	12.12	MST configuration entities	245
48	12.12.1	The MSTI List	245
49	12.12.2	The FID to MSTID Allocation Table	247
50	12.12.3	The MST Configuration Table	248
51	12.13	Provider Bridge management	250
52	12.13.1	Provider Bridge Port Type managed object	251
53	12.13.2	Network Port Configuration managed object	253
54			

1	12.13.3 Customer Edge Port Configuration managed object	253
2	12.14 CFM entities	257
3	12.15 Backbone Core Bridge management	273
4	12.16 Backbone Edge Bridge management.....	273
5	12.16.1 BEB configuration managed object.....	275
6	12.16.2 BEB/PB/VLAN Bridge Port configuration managed object	278
7	12.16.3 VIP configuration managed object	278
8	12.16.4 PIP configuration managed object.....	280
9	12.16.5 CBP Configuration managed object	286
10	12.17 DDCFM entities.....	288
11	12.17.1 DDCFM Stack managed object	288
12	12.17.2 Reflection Responder managed object	289
13	12.17.3 RFM Receiver managed object.....	292
14	12.17.4 Decapsulator Responder managed object	293
15	12.17.5 SFM Originator managed object.....	296
16	12.18 PBB-TE Protection Switching managed objects	298
17	12.18.1 TE protection group list managed object.....	298
18	12.19 TPMR managed objects.....	302
19	12.19.1 TPMR management entity	302
20	12.19.2 MAC and PHY entities	304
21	12.19.3 Forwarding Process.....	304
22	12.19.4 MAC status propagation entity	310
23	12.20 Management entities for forwarding and queueing for time-sensitive streams	312
24	12.20.1 The Bandwidth Availability Parameter Table	312
25	12.20.2 The Transmission Selection Algorithm Table	312
26	12.20.3 The Priority Regeneration Override Table	313
27	12.21 Congestion notification managed objects	313
28	12.22 SRP entities.....	318
29	12.22.1 SRP Bridge Base Table.....	318
30	12.22.2 SRP Bridge Port Table.....	318
31	12.22.3 SRP Latency Parameter Table	319
32	12.22.4 SRP Stream Table.....	320
33	12.22.5 SRP Reservations Table.....	320
34		
35	13. Spanning Tree Protocols	322
36		
37	13.1 Protocol design requirements.....	323
38	13.2 Protocol support requirements	323
39	13.2.1 MSTP support requirements	324
40	13.3 Protocol design goals	324
41	13.4 RSTP overview	324
42	13.4.1 Computation of the active topology.....	325
43	13.4.2 Example topologies.....	327
44	13.5 MSTP overview	330
45	13.5.1 Example topologies.....	331
46	13.5.2 Relationship of MSTP to RSTP.....	334
47	13.5.3 Modeling an MST Region as a single bridge	334
48	13.6 Compatibility and interoperability	335
49	13.6.1 Designated Port selection.....	335
50	13.6.2 Force Protocol Version.....	335
51	13.7 MST Configuration Identifier	336
52	13.8 Spanning Tree Priority Vectors	337
53	13.9 CIST Priority Vector calculations	339
54		

1	13.10 MST Priority Vector calculations	340
2	13.11 Port Role assignments.....	342
3	13.12 Stable connectivity.....	342
4	13.13 Communicating Spanning Tree information.....	343
5	13.14 Changing Spanning Tree information.....	345
6	13.15 Changing Port States with RSTP or MSTP	345
7	13.15.1 Subtree connectivity and priority vectors	346
8	13.15.2 Root Port transition to Forwarding.....	346
9	13.15.3 Designated Port transition to Forwarding.....	346
10	13.15.4 Master Port transition to Forwarding.....	347
11	13.16 Managing spanning tree topologies	349
12	13.17 Updating learned station location information	351
13	13.18 Managing reconfiguration.....	353
14	13.19 Partial and disputed connectivity.....	354
15	13.20 In-service upgrades	354
16	13.21 Fragile bridges	355
17	13.22 Spanning tree protocol state machines.....	356
18	13.23 State machine timers	358
19	13.23.1 edgeDelayWhile.....	359
20	13.23.2 fdWhile	359
21	13.23.3 helloWhen.....	359
22	13.23.4 mdelayWhile.....	359
23	13.23.5 rbWhile	359
24	13.23.6 rcvdInfoWhile	360
25	13.23.7 rrWhile	360
26	13.23.8 tcDetected	360
27	13.23.9 tcWhile.....	360
28	13.23.10pseudoInfoHelloWhen	360
29	13.24 Per bridge variables	360
30	13.24.1 BridgeIdentifier.....	361
31	13.24.2 BridgePriority	361
32	13.24.3 BridgeTimes.....	361
33	13.24.4 ForceProtocolVersion.....	361
34	13.24.5 MigrateTime	361
35	13.24.6 MstConfigId.....	362
36	13.24.7 rootPortId	362
37	13.24.8 rootPriority.....	362
38	13.24.9 rootTimes	362
39	13.24.10TxHoldCount	362
40	13.25 Per port variables	362
41	13.25.1 AdminEdge	364
42	13.25.2 ageingTime	364
43	13.25.3 agree.....	364
44	13.25.4 agreed.....	364
45	13.25.5 AutoEdge	364
46	13.25.6 AutoIsolate.....	364
47	13.25.7 designatedPriority	365
48	13.25.8 designatedTimes	365
49	13.25.9 disputed.....	365
50	13.25.10enableBPDURx	365
51	13.25.11enableBPDUTx	365
52	13.25.12ExternalPortPathCost.....	365
53	13.25.13isL2gp	365
54	13.25.14isolate.....	365

1	13.25.15fdbFlush	366
2	13.25.16forward.....	366
3	13.25.17forwarding.....	366
4	13.25.18infoInternal.....	366
5	13.25.19infoIs	366
6	13.25.20InternalPortPathCost.....	366
7	13.25.21learn	366
8	13.25.22learning	367
9	13.25.23master.....	367
10	13.25.24mastered	367
11	13.25.25mcheck	367
12	13.25.26msgPriority.....	367
13	13.25.27msgTimes	367
14	13.25.28newInfo	367
15	13.25.29newInfoMsti.....	368
16	13.25.30operEdge	368
17	13.25.31portEnabled.....	368
18	13.25.32portId.....	368
19	13.25.33portPriority.....	368
20	13.25.34portTimes	368
21	13.25.35proposed	368
22	13.25.36proposing	368
23	13.25.37pseudoRootId	369
24	13.25.38rcvdBPDU.....	369
25	13.25.39rcvdInfo.....	369
26	13.25.40rcvdInternal.....	369
27	13.25.41rcvdMsg	369
28	13.25.42rcvdRSTP.....	369
29	13.25.43rcvdSTP	369
30	13.25.44rcvdTc	369
31	13.25.45rcvdTcAck.....	369
32	13.25.46rcvdTcn	369
33	13.25.47reRoot.....	369
34	13.25.48reselect	369
35	13.25.49restrictedRole	370
36	13.25.50restrictedTcn.....	370
37	13.25.51role	370
38	13.25.52selected.....	370
39	13.25.53selectedRole	370
40	13.25.54sendRSTP.....	370
41	13.25.55sync	370
42	13.25.56synced	370
43	13.25.57tcAck.....	370
44	13.25.58tcProp.....	371
45	13.25.59tick	371
46	13.25.60txCount.....	371
47	13.25.61updtInfo.....	371
48	13.26 State machine conditions and parameters.....	371
49	13.26.1 allSynced.....	371
50	13.26.2 allTransmitReady.....	372
51	13.26.3 cist.....	372
52	13.26.4 cistRootPort	372
53	13.26.5 cistDesignatedPort	372
54	13.26.6 EdgeDelay.....	372

1	13.26.7 forwardDelay	372
2	13.26.8 FwdDelay	372
3	13.26.9 HelloTime	372
4	13.26.10msti	372
5	13.26.11MaxAge	372
6	13.26.12mstiDesignatedOrTCpropagatingRootPort.....	372
7	13.26.13mstiMasterPort.....	373
8	13.26.14operPointToPoint	373
9	13.26.15rcvdAnyMsg	373
10	13.26.16rcvdCistMsg.....	373
11	13.26.17rcvdMstiMsg.....	373
12	13.26.18reRooted	373
13	13.26.19rstpVersion	373
14	13.26.20stpVersion.....	373
15	13.26.21updtCistInfo	373
16	13.26.22updtMstiInfo	373
17	13.27 State machine procedures	373
18	13.27.1 betterorsameInfo(newInfol)	374
19	13.27.2 clearAllRcvdMsgs().....	375
20	13.27.3 clearReselectTree()	375
21	13.27.4 disableForwarding().....	375
22	13.27.5 disableLearning()	375
23	13.27.6 enableForwarding().....	375
24	13.27.7 enableLearning()	375
25	13.27.8 fromSameRegion().....	375
26	13.27.9 newTcDetected()	375
27	13.27.10newTcWhile()	375
28	13.27.11pseudoRcvMsgs()	376
29	13.27.12rcvInfo()	376
30	13.27.13rcvMsgs()	377
31	13.27.14recordAgreement().....	377
32	13.27.15recordDispute()	377
33	13.27.16recordMastered().....	378
34	13.27.17recordPriority()	378
35	13.27.18recordProposal().....	378
36	13.27.19recordTimes().....	378
37	13.27.20setReRootTree()	378
38	13.27.21setSelectedTree().....	378
39	13.27.22setSyncTree()	378
40	13.27.23setTcFlags().....	378
41	13.27.24setTcPropTree().....	379
42	13.27.25syncMaster()	379
43	13.27.26txConfig().....	379
44	13.27.27txRstp()	379
45	13.27.28txTcn().....	380
46	13.27.29updtBPDUVersion().....	380
47	13.27.30updtRcvdInfoWhile().....	380
48	13.27.31updtRolesTree()	380
49	13.27.32uptRolesDisabledTree()	382
50	13.28 The Port Timers state machine.....	382
51	13.29 Port Receive state machine	382
52	13.30 Port Protocol Migration state machine	383
53	13.31 Bridge Detection state machine	383
54	13.32 Port Transmit state machine.....	384

1	13.33 Port Information state machine.....	385
2	13.34 Port Role Selection state machine	386
3	13.35 Port Role Transitions state machine.....	386
4	13.36 Port State Transition state machine.....	390
5	13.36.1 Port State transitions for the CIST and MSTIs	390
6	13.37 Topology Change state machine	391
7	13.38 Layer 2 Gateway Port Receive state machine	392
8	13.39 Customer Edge Port Spanning Tree operation.....	392
9	13.39.1 Provider Edge Port operPointToPointMAC and operEdge	392
10	13.39.2 updtRolesTree()	393
11	13.39.3 setReRootTree(), setSyncTree(), setTcPropTree().....	393
12	13.39.4 allSynced, reRooted	393
13	13.39.5 Configuration parameters	393
14	13.40 Virtual Instance Port Spanning Tree operation.....	394
15		
16	14. Use of BPDUs by MSTP	395
17		
18	14.1 BPDUs Structure	395
19	14.1.1 Transmission and representation of octets.....	395
20	14.1.2 Components	395
21	14.2 Encoding of parameter types	395
22	14.2.1 Encoding of Port Role values	396
23	14.2.2 Allocation and encoding of Bridge Identifiers	396
24	14.2.3 Allocation and encoding of Port Identifiers.....	396
25	14.2.4 Encoding of External Root Path Cost	396
26	14.2.5 Encoding of Internal Root Path Cost	396
27	14.2.6 Encoding of Hop Counts.....	397
28	14.3 BPDUs formats and parameters	397
29	14.3.1 STP BPDUs	397
30	14.3.2 RST BPDUs.....	397
31	14.3.3 MST BPDUs.....	397
32	14.4 Validation of received BPDUs	398
33	14.5 Transmission of BPDUs	398
34	14.6 Encoding and decoding of STP Configuration, RST, and MST BPDUs	399
35	14.6.1 MSTI Configuration Messages.....	400
36		
37	15. Support of the MAC Service by Provider Bridged Networks	402
38		
39	15.1 Service transparency	402
40	15.2 Customer service interfaces	403
41	15.3 Port-based service interface	403
42	15.4 C-tagged service interface	404
43	15.5 S-tagged service interface.....	405
44	15.6 Service instance segregation.....	405
45	15.7 Service instance selection and identification	406
46	15.8 Service priority selection	407
47	15.9 Service access protection	407
48	15.10 Connectivity Fault Management.....	407
49	15.11 Data driven and data dependent connectivity fault management (DDCFM)	408
50		
51		
52	16. Principles of Provider Bridged Network operation	409
53		
54		

1	16.1	Provider Bridged Network overview	409
2	16.2	Provider Bridged Network	410
3	16.3	Service instance connectivity	411
4	16.4	Service provider learning of customer end station addresses	412
5	16.5	Detection of connectivity loops through attached networks	412
6	16.6	Network management	413
7			
8	17.	Management Information Base (MIB)	414
9			
10	17.1	Internet Standard Management Framework	414
11	17.2	Structure of the MIB	414
12	17.2.1	Structure of the IEEE8021-TC MIB	415
13	17.2.2	Structure of the IEEE8021-BRIDGE MIB	416
14	17.2.3	Structure of the IEEE8021-SPANNING-TREE MIB	421
15	17.2.4	Structure of the IEEE8021-Q-BRIDGE MIB	423
16	17.2.5	Structure of the IEEE8021-PB MIB	430
17	17.2.6	Structure of the IEEE8021-MSTP MIB	431
18	17.2.7	Structure of the IEEE8021-CFM MMIB	435
19	17.2.8	Structure of the IEEE8021-PBB MIB	440
20	17.2.9	Structure of the IEEE8021-DDCFM MIBs	443
21	17.2.10	Structure of the IEEE8021-PBBTE MIB	445
22	17.2.11	Structure of the TPMR MIB	448
23	17.2.12	Structure of the IEEE8021-FQTSS MIB	450
24	17.2.13	Structure of the Congestion Notification MIB	450
25	17.2.14	Structure of the IEEE8021-SRP MIB	453
26	17.3	Relationship to other MIBs	455
27	17.3.1	Relationship of the IEEE8021-TC MIB to other MIB modules	455
28	17.3.2	Relationship of the IEEE8021-BRIDGE MIB to other MIB modules	455
29	17.3.3	Relationship of the IEEE8021-RSTP MIB to other MIB modules	458
30	17.3.4	Relationship of the IEEE8021-Q-BRIDGE MIB to other MIB modules	458
31	17.3.5	Relationship of the IEEE8021-PB-BRIDGE MIB to other MIB modules	459
32	17.3.6	Relationship of the IEEE8021-MSTP MIB to other MIB modules	460
33	17.3.7	Relationship of the IEEE8021-CFM MIB to other MIB modules	460
34	17.3.8	Relationship of the IEEE8021-PBB MIB to other MIB modules	461
35	17.3.9	Relationship of the IEEE8021-DDCFM to other MIB modules	462
36	17.3.10	Relationship of the IEEE8021-PBBTE MIB to other MIB modules	462
37	17.3.11	Relationship of the TPMR MIB to other MIB modules	463
38	17.3.12	Relationship of the IEEE8021-FQTSS MIB to other MIB modules	463
39	17.3.14	Relationship of the IEEE8021-SRP MIB to other MIB modules	464
40	17.4	Security considerations	464
41	17.4.1	Security considerations of the IEEE8021-TC MIB	464
42	17.4.2	Security considerations of the IEEE8021-BRIDGE MIB	464
43	17.4.3	Security considerations of the IEEE8021-SPANNING-TREE MIB	465
44	17.4.4	Security considerations of the IEEE8021-Q-BRIDGE MIB	466
45	17.4.5	Security considerations of the IEEE8021-PB MIB	467
46	17.4.6	Security considerations of the IEEE8021-MSTP MIB	467
47	17.4.7	Security considerations of the IEEE8021-CFM MIB	468
48	17.4.8	Security considerations of the IEEE8021-PBB MIB	470
49	17.4.9	Security considerations of the IEEE8021-DDCFM MIB	471
50	17.4.10	Security considerations of the IEEE8021-PBBTE MIB	471
51	17.4.11	Security considerations of the TPMR MIB	472
52	17.4.12	Security considerations of the IEEE8021-FQTSS MIB	473
53	17.4.13	Security considerations of the Congestion Notification MIB	473
54			

1	17.4.14 Security considerations of the IEEE8021-SRP MIB	475
2	17.5 Dynamic component and Port creation.....	475
3	17.5.1 Overview of the dynamically created Bridge entities.....	475
4	17.5.2 Component creation.....	476
5	17.5.3 Port creation.....	477
6	17.6 MIB operations for service interface configuration.....	484
7	17.6.1 Provisioning Provider Bridged Network service interfaces	484
8	17.6.2 Provisioning Backbone Bridged Network service interfaces	488
9	17.7 MIB modules	494
10	17.7.1 Definitions for the IEEE8021-TC MIB module	494
11	17.7.2 Definitions for the IEEE8021-BRIDGE MIB module	503
12	17.7.3 Definitions for the IEEE8021-SPANNING-TREE MIB module.....	538
13	17.7.4 Definitions for the IEEE8021-Q-BRIDGE MIB module	555
14	17.7.5 Definitions for the IEEE8021-PB MIB module	595
15	17.7.6 Definitions for the IEEE8021-MSTP MIB module.....	608
16	17.7.7 Definitions for the IEEE8021-CFM MIB module.....	633
17	17.7.8 Definitions for the IEEE8021-PBB MIB module.....	717
18	17.7.9 Definitions for the IEEE8021-DDCFM MIB module	739
19	17.7.10 Definitions for the IEEE8021-PBBTE MIB module.....	756
20	17.7.11 Definitions for the TPMR MIB module	773
21	17.7.12 Definitions for the IEEE8021-FQTSS MIB module	787
22	17.7.13 Congestion Notification MIB module	798
23	17.7.14 Definitions of the IEEE8021-SRP MIB module.....	832
24		
25	18. Principles of Connectivity Fault Management operation	848
26		
27	18.1 Maintenance Domains and Domain Service Access Points	849
28	18.2 Service instances and Maintenance Associations.....	851
29	18.3 Maintenance Domain Levels	852
30		
31	19. Connectivity Fault Management Entity operation.....	856
32		
33		
34	19.1 Maintenance Points.....	856
35	19.2 Maintenance association End Point	856
36	19.2.1 MEP identification	857
37	19.2.2 MEP functions	858
38	19.2.3 MEP architecture	858
39	19.2.4 MP Type Demultiplexer	858
40	19.2.5 MP Multiplexer.....	860
41	19.2.6 MP Level Demultiplexer	860
42	19.2.7 MP OpCode Demultiplexer	860
43	19.2.8 MEP Continuity Check Receiver.....	860
44	19.2.9 MEP Continuity Check Initiator	861
45	19.2.10 MP Loopback Responder.....	861
46	19.2.11 MEP Loopback Initiator	861
47	19.2.12 MEP Linktrace Initiator	861
48	19.2.13 MEP LTI SAP.....	862
49	19.2.14 MEP Linktrace SAP.....	862
50	19.2.15 MEP CCM Database.....	862
51	19.2.16 MEP Fault Notification Generator.....	862
52	19.2.17 MEP Decapsulator Responder	862
53	19.2.18 MEP RFM Receiver.....	862
54	19.3 MIP Half Function	863

1	19.3.1	MHF identification	863
2	19.3.2	MHF functions	863
3	19.3.3	MHF architecture	864
4	19.3.4	MHF Level Demultiplexer.....	864
5	19.3.5	MHF Type Demultiplexer	865
6	19.3.6	MHF OpCode Demultiplexer	865
7	19.3.7	MHF Multiplexer	865
8	19.3.8	MHF Loopback Responder.....	865
9	19.3.9	MHF Continuity Check Receiver	865
10	19.3.10	MIP CCM Database.....	865
11	19.3.11	MHF Linktrace SAP	865
12	19.3.12	MHF Decapsulator Responder.....	865
13	19.3.13	MHF RFM Receiver	865
14	19.4	Maintenance Point addressing	866
15	19.5	Linktrace Output Multiplexer	866
16	19.6	Linktrace Responder	867
17			
18	20.	Connectivity Fault Management protocols.....	869
19			
20	20.1	Continuity Check protocol.....	870
21	20.2	Loopback protocol	873
22	20.3	Linktrace protocol.....	875
23	20.4	Connectivity Fault Management state machines	878
24	20.5	CFM state machine timers	880
25	20.6	CFM procedures	882
26	20.7	Maintenance Domain variable	882
27	20.8	Maintenance Association variables	882
28	20.9	MEP variables.....	882
29	20.9.8	presentTraffic.....	884
30	20.9.9	presentmmLoc	884
31	20.10	MEP Continuity Check Initiator variables.....	884
32	20.11	MEP Continuity Check Initiator procedures	885
33	20.12	MEP Continuity Check Initiator state machine	886
34	20.13	MHF Continuity Check Receiver variables.....	886
35	20.14	MHF Continuity Check Receiver procedures.....	886
36	20.15	MHF Continuity Check Receiver state machine	887
37	20.16	MEP Continuity Check Receiver variables	888
38	20.17	MEP Continuity Check Receiver procedures	890
39	20.18	MEP Continuity Check Receiver state machine.....	891
40	20.19	Remote MEP variables	891
41	20.20	Remote MEP state machine.....	893
42	20.21	Remote MEP Error variables	893
43	20.22	Remote MEP Error state machine	894
44	20.23	MEP Cross Connect variables	894
45	20.24	MEP Cross Connect state machine	895
46	20.25	MEP Mismatch variables	895
47	20.25.1	mmCCMreceived.....	896
48	20.25.2	mmCCMdefect.....	896
49	20.25.3	mmCCMTime	896
50	20.25.4	disableLocdefect	896
51	20.25.5	mmLocdefect	896
52	20.26	MEP Mismatch state machines.....	896
53	20.27	MP Loopback Responder variables	896
54			

1	20.28MP Loopback Responder procedures	898
2	20.29MP Loopback Responder state machine.....	899
3	20.30MEP Loopback Initiator variables.....	899
4	20.31MEP Loopback Initiator transmit procedures.....	900
5	20.32MEP Loopback Initiator transmit state machine	901
6	20.33MEP Loopback Initiator receive procedures	902
7	20.34MEP Loopback Initiator receive state machine	902
8	20.35MEP Fault Notification Generator variables	902
9	20.36MEP Fault Notification Generator procedures	904
10	20.37MEP Fault Notification Generator state machine.....	904
11	20.38 MEP Mismatch Fault Notification Generator variables	904
12	20.39 MEP Mismatch Fault Notification Generator procedures	906
13	20.40 MEP Mismatch Fault Notification Generator state machine.....	906
14	20.41MEP Linktrace Initiator variables.....	907
15	20.42MEP Linktrace Initiator procedures	909
16	20.43MEP Linktrace Initiator receive variables	910
17	20.44MEP Linktrace Initiator receive procedures	910
18	20.45MEP Linktrace Initiator receive state machine.....	910
19	20.46Linktrace Responder variables.....	910
20	20.47LTM Receiver procedures	911
21	20.48LTM Receiver state machine	917
22	20.49LTR Transmitter procedure	917
23	20.50LTR Transmitter state machine	918
24	20.51CFM PDU validation and versioning	919
25	20.52PDU identification	922
26	20.53Use of transaction IDs and sequence numbers	922
27		
28	21.Encoding of CFM Protocol Data Units.....	924
29		
30	21.1Structure, representation, and encoding.....	924
31	21.2CFM encapsulation	924
32	21.3CFM request and indication parameters	925
33	21.4Common CFM Header.....	926
34	21.5TLV Format	927
35	21.6Continuity Check Message format	932
36	21.7Loopback Message and Loopback Reply formats.....	937
37	21.7.4 Additional LBM/LBR TLVs	938
38	21.7.5 PBB-TE MIP TLV	938
39	21.8Linktrace Message Format.....	939
40	21.9Linktrace Reply Format	941
41		
42		
43	22. Connectivity Fault Management in systems.....	947
44		
45	22.1 CFM shims in Bridges	947
46	22.1.1 Preliminary positioning of Maintenance Points.....	947
47	22.1.2 CFM and the Forwarding Process	948
48	22.1.3 Up/Down separation of Maintenance Points	949
49	22.1.4 Service instances over multiple Bridges	952
50	22.1.5 Multiple VID service instances.....	952
51	22.1.6 Untagged CFM PDUs.....	954
52	22.1.7 Maintenance Points and non-VLAN aware Bridges.....	954
53	22.1.8 Maintenance Points and other standards.....	954
54	22.1.9 CFM and IEEE 802.3 Clause 57 OAM	957

1	22.2	Maintenance Entity creation	957
2	22.2.1	Creating Maintenance Domains and Maintenance Associations.....	957
3	22.2.2	Creating MEPs	958
4	22.2.3	Creating MIPs	959
5	22.2.4	CFM configuration errors	961
6	22.3	MPs, Ports, and MD Level assignment.....	961
7	22.4	Stations and Connectivity Fault Management	962
8	22.5	Scalability of Connectivity Fault Management	962
9	22.6	CFM in Provider Bridges.....	964
10	22.6.1	Maintenance Points and C-VLAN components.....	964
11	22.6.2	Maintenance C-VLAN on a Port-based service interface	964
12	22.6.3	Maintenance C-VLAN on a C-tagged service interface	965
13	22.7	Management Port MEPs and CFM in the enterprise environment.....	966
14	22.8	Implementing CFM on existing Bridges	968
15			
16	23.	MAC status propagation	969
17			
18	23.1	Model of operation.....	970
19	23.1.1	MAC Status Shim	971
20	23.1.2	Relationship of Connectivity Fault Management to the MAC Status Shim.....	972
21	23.2	MAC status protocol (MSP) overview	972
22	23.3	MAC status protocol state machines	975
23	23.4	State machine timers	977
24	23.4.1	linkNotifyWhen	977
25	23.4.2	linkNotifyWhile	978
26	23.4.3	macNotifyWhile.....	978
27	23.4.4	macRecoverWhile.....	978
28	23.5	MSP performance parameters.....	978
29	23.5.1	LinkNotify	978
30	23.5.2	LinkNotifyWait.....	978
31	23.5.3	LinkNotifyRetry.....	978
32	23.5.4	MACNotify	978
33	23.5.5	MACNotifyTime	978
34	23.5.6	MACRecoverTime.....	978
35	23.6	State machine variables	979
36	23.6.1	BEGIN	979
37	23.6.2	addConfirmed	979
38	23.6.3	disableMAC	979
39	23.6.4	disabledMAC	979
40	23.6.5	disableMSS	979
41	23.6.6	lossConfirmed	979
42	23.6.7	macOperational	980
43	23.6.8	mssOperational	980
44	23.6.9	prop	980
45	23.6.10	rxAck	980
46	23.6.11	rxAdd	980
47	23.6.12	rxAddConfirm.....	980
48	23.6.13	rxLoss.....	980
49	23.6.14	rxLossConfirm	980
50	23.6.15	txAck.....	980
51	23.6.16	txAdd	980
52	23.6.17	txAddConfirm	980
53	23.6.18	txLoss.....	980
54			

1	23.6.19 txLossConfirm	981
2	23.7 State machine procedures	981
3	23.8 Status Transition state machine	981
4	23.9 Status Notification state machine	981
5	23.10 Receive Process	981
6	23.11 Transmit Process.....	981
7	23.12 Management of MSP	982
8	23.13 MSPDU transmission, addressing, and protocol identification.....	983
9	23.13.1 Destination MAC Address.....	983
10	23.13.2 Source MAC Address	983
11	23.13.3 Priority	983
12	23.13.4 EtherType use and encoding.....	983
13	23.14 Representation and encoding of octets	984
14	23.15 MSPDU structure.....	984
15	23.15.1 Protocol Version	984
16	23.15.2 Packet Type.....	984
17	23.16 Validation of received MSPDUs	985
18	23.17 Other MSP participants.....	985
19		
20	24. <Reserved for a future amendment>	986
21		
22	25. Support of the MAC Service by Provider Backbone Bridged Networks	987
23		
24		
25	25.1 Service transparency	989
26	25.2 Customer service interface.....	989
27	25.3 Port-based service interface	990
28	25.4 S-tagged service interface.....	991
29	25.5 I-tagged service interface.....	994
30	25.6 Service instance segregation	996
31	25.7 Service instance selection and identification	996
32	25.8 Service priority and drop eligibility selection.....	996
33	25.9 Service access protection	997
34	25.9.1 Class II redundant LANs access protection.....	999
35	25.9.2 Class III simple redundant LANs and nodes access protection.....	1000
36	25.10 Support of the MAC Service by a PBB-TE Region	1001
37	25.10.1 Provisioning TESIS	1002
38	25.10.2 ESP forwarding behavior.....	1003
39	25.11 Transparent service interface	1004
40		
41	26. Principles of Provider Backbone Bridged Network operation	1006
42		
43	26.1 Provider Backbone Bridged Network overview	1006
44	26.2 Provider Backbone Bridged Network example	1007
45	26.3 Backbone VLAN connectivity.....	1009
46	26.4 Backbone addressing	1010
47	26.4.1 Learning individual backbone addresses at a PIP.....	1011
48	26.4.2 Translating backbone destination addresses at a CBP.....	1011
49	26.4.3 Backbone addressing considerations for CFM Maintenance Points	1012
50	26.5 Detection of connectivity loops through attached networks.....	1012
51	26.6 Scaling of Provider Backbone Bridges	1013
52	26.6.1 Hierarchal PBBNs.....	1013
53	26.6.2 Peer PBBNs	1013
54		

1	26.7 Network Management.....	1013
2	26.8 Connectivity Fault Management in Provider Backbone Bridges	1014
3	26.8.1 CFM over Port-based and S-tagged Service Interfaces	1016
4	26.8.2 Connectivity Fault Management over I-tagged Service Interfaces	1017
5	26.8.3 Connectivity Fault Management over hierarchal E-NNI.....	1019
6	26.8.4 Connectivity Fault Management over peer E-NNI.....	1020
7	26.9 Connectivity Fault Management in a PBB-TE Region	1022
8	26.9.1 Addressing PBB-TE MEPs.....	1022
9	26.9.2 TESI identification.....	1022
10	26.9.3 PBB-TE MEP placement in a Bridge Port.....	1023
11	26.9.4 PBB-TE MIP placement in a Bridge Port.....	1023
12	26.9.5 TESI Maintenance Domains	1023
13	26.10 Protection switching for point-to-point TESIs.....	1026
14	26.10.1 Introduction.....	1026
15	26.10.2 1:1 point-to-point TESI protection switching.....	1027
16	26.10.3 Protection Switching state machines	1030
17	26.11 Mismatch defect.....	1035
18		
19	27. <Reserved for a future amendment>	1037
20		
21	28. <Reserved for a future amendment>	1038
22		
23		
24	29. DDCFM operations and protocols	1039
25		
26	29.1 Principles of DDCFM operation.....	1039
27	29.1.1 Data driven and data dependent faults (DDF)	1039
28	29.1.2 Basic principle to diagnose and isolate DDFs	1039
29	29.2 DDCFM Entity operation	1042
30	29.2.1 DDCFM implementation	1042
31	29.2.2 Forward Path Test Reflection Responder	1043
32	29.2.3 Reflection Responder related parameters	1044
33	29.2.4 Reflection Target and RFM Receiver.....	1045
34	29.2.5 Return path test related parameters.....	1046
35	29.2.6 Decapsulator Responder	1046
36	29.2.7 SFM Originator.....	1047
37	29.3 DDCFM protocols	1047
38	29.3.1 Reflection Responder variables	1047
39	29.3.2 RR Filter Procedures.....	1049
40	29.3.3 RR Encapsulation Procedures.....	1050
41	29.3.4 RR Transmit procedure.....	1051
42	29.3.5 Reflection Responder related state machines	1052
43	29.3.6 RFM Receiver variables	1053
44	29.3.7 RFM Receiver procedure.....	1054
45	29.3.8 Decapsulator Responder variables.....	1055
46	29.3.9 Decapsulator Responder procedures.....	1056
47	29.3.10 Decapsulator Responder state machine	1057
48	29.4 Encoding of DDCFM Protocol Data Units.....	1057
49	29.4.1 RFM and SFM Header.....	1057
50	29.4.2 RFM format	1057
51	29.4.3 SFM format.....	1059
52		
53	30.Principles of congestion notification	1060
54		

1	30.1 Congestion notification design requirements	1060
2	30.2 Quantized Congestion Notification protocol	1062
3	30.3 Congestion Controlled Flow	1066
4	30.4 Congestion Notification Priority Value	1067
5	30.5 Congestion Notification Tag	1067
6	30.6 Congestion Notification Domain	1067
7	30.7 Multicast data	1068
8	30.8 Congestion notification and additional tags	1068
9		
10	31. Congestion notification entity operation	1070
11		
12	31.1 Congestion aware Bridge Forwarding Process	1070
13	31.2 Congestion aware end station functions	1071
14		
15	32. Congestion notification protocol	1077
16		
17		
18	32.1 Congestion Notification Domain operations	1077
19	32.2 CN component variables	1080
20	32.3 Congestion notification per-CNPV variables	1081
21	32.4 CN defense per-Port per-CNPV variables	1083
22	32.5 Congestion Notification Domain defense procedures	1086
23	32.6 Congestion Notification Domain defense state machine	1087
24	32.7 Congestion notification protocol	1087
25	32.8 Congestion Point variables	1088
26	32.9 Congestion Point procedures	1090
27	32.10 Reaction Point per-Port per-CNPV variables	1093
28	32.11 Reaction Point group variables	1093
29	32.12 Reaction Point timer	1095
30	32.13 Reaction Point variables	1095
31	32.14 Reaction Point procedures	1096
32	32.15 RP rate control state machine	1098
33	32.16 Congestion notification and encapsulation interworking function	1100
34		
35	33. Encoding of congestion notification Protocol Data Units	1102
36		
37		
38	33.1 Structure, representation, and encoding	1102
39	33.2 Congestion Notification Tag format	1102
40	33.3 Congestion Notification Message	1103
41	33.4 Congestion Notification Message PDU format	1104
42		
43	34. Forwarding and queuing for time-sensitive streams	1107
44		
45	34.1 Overview	1107
46	34.2 Detection of SRP domains	1107
47	34.3 The bandwidth availability parameters	1108
48	34.3.1 Relationships among bandwidth availability parameters	1108
49	34.3.2 Bandwidth availability parameter management	1109
50	34.4 Deriving actual bandwidth requirements from the size of the MSDU	1109
51	34.5 Mapping priorities to traffic classes for time-sensitive streams	1110
52	34.6 End station behavior	1112
53	34.6.1 Talker behavior	1112
54	34.6.2 Listener behavior	1113

1	35. Stream Registration Protocol (SRP)	1114
2		
3	35.1 Multiple Stream Registration Protocol (MSRP).....	1115
4	35.1.1 MSRP and Shared Media.....	1116
5	35.1.2 Behavior of end stations	1116
6	35.1.3 Behavior of Bridges	1118
7	35.2 Definition of the MSRP application	1118
8	35.2.1 Definition of internal state variables.....	1118
9	35.2.2 Definition of MRP protocol elements.....	1120
10	35.2.3 Provision and support of Stream registration service	1132
11	35.2.4 MSRP Attribute Propagation.....	1136
12	35.2.5 Operational reporting and statistics	1140
13	35.2.6 Encoding	1140
14	35.2.7 Attribute value support requirements	1141
15		
16	Annex A	1143
17		
18	(normative)PICS proforma—Bridge implementations.....	1143
19		
20	Annex B	1195
21		
22	(normative)PICS proforma—End station implementations	1195
23		
24	Annex C (normative)DMN (Designated MSRP Node) Implementations	1208
25		
26	Annex D	1225
27		
28	(normative)IEEE 802.1 Organizationally Specific TLVs.....	1225
29		
30	Annex E	1270
31		
32	(normative)Notational conventions used in state diagrams	1270
33		
34	Annex F	1272
35		
36	(informative)Shared and Independent VLAN Learning.....	1272
37		
38	Annex G	1281
39		
40	(informative)MAC method dependent aspects of VLAN support.....	1281
41		
42	Annex H	1283
43		
44	(informative)Interoperability considerations	1283
45		
46	Annex I	1291
47		
48	(informative)Priority and drop precedence.....	1291
49		
50	Annex J	1299
51		
52		
53		
54		

1	(informative)Connectivity Fault Management protocol design and use	1299
2		
3	Annex K	1307
4		
5	(informative)TPMR use cases	1307
6		
7	Annex L	1312
8		
9	(informative)Operation of the credit-based shaper algorithm	1312
10		
11	Annex M	1329
12		
13	(informative)Bibliography	1329
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		

Figures

1		
2		
3	Figure 6-1—Internal organization of the MAC sublayer	47
4	Figure 6-2—MAC entities, the MAC Service, and MAC Service users (clients).....	49
5	Figure 6-3—An interface stack.....	50
6	Figure 6-4—Provider Instance Ports	74
7	Figure 6-5—B-Component Customer Backbone Port.....	77
8	Figure 6-6—Example of operation of port-and-protocol based classification	81
9	Figure 6-7—Service access priority selection	84
10	Figure 6-8—Two back-to-back EISS Multiplex Entities	90
11	Figure 6-9—Two back-to-back Backbone Service Instance Multiplex Entities	91
12	Figure 6-10—Backbone Service Instance Multiplex Entities with example CFM shims	91
13	Figure 6-11—Two back-to-back Up and Down TESI Multiplex Entities.....	94
14	Figure 6-12—Supporting the ISS with signaled priority.....	95
15	Figure 7-1—VLAN Bridging overview	98
16	Figure 8-1—A Bridged Local Area Network	104
17	Figure 8-2—VLAN-aware Bridge architecture	106
18	Figure 8-3—Relaying MAC frames	108
19	Figure 8-4—Observation of network traffic	108
20	Figure 8-5—Operation of Spanning Tree protocol.....	109
21	Figure 8-6—Operation of MRP	109
22	Figure 8-7—Management Port transmission and reception	110
23	Figure 8-8—Bridge Port Transmit and Receive	112
24	Figure 8-9—TPMR Port Transmit and Receive.....	112
25	Figure 8-10—Forwarding Process functions.....	114
26	Figure 8-11—Logical points of attachment of the Higher Layer and Relay Entities	142
27	Figure 8-12—Effect of control information on the forwarding path.....	143
28	Figure 8-13—Per-Port points of attachment.....	143
29	Figure 8-14—Single point of attachment—relay permitted	144
30	Figure 8-15—Single point of attachment—relay not permitted.....	144
31	Figure 8-16—Effect of Port State.....	144
32	Figure 8-17—Controlled and Uncontrolled Port connectivity	145
33	Figure 8-18—Ingress/egress control information in the forwarding path	146
34	Figure 9-1—VLAN TCI format	150
35	Figure 9-3—I-TAG TCI Format.....	151
36	Figure 10-1—Example—Attribute value propagation from one station	154
37	Figure 10-2—Example—Attribute value propagation from two stations	154
38	Figure 10-3—Example—Registrations as pointers to the sources of declarations	155
39	Figure 10-4—MRP architecture	157
40	Figure 10-5—Format of the major components of an MRPDU.....	180
41	Figure 10-6—Operation of MMRP for a single VLAN Context.....	186
42	Figure 10-7—Example Directed Graph.....	187
43	Figure 10-8—Example of MMRP propagation in a VLAN Context	189
44	Figure 11-1—Operation of MVRP	197
45	Figure 12-1—Relationships among CFM managed objects.....	258
46	Figure 12-2—Relationship among BEB managed objects	274
47	Figure 13-1—Diagrammatic conventions for spanning tree topologies.....	327
48	Figure 13-2—Physical topology and active topology	328
49	Figure 13-3—Port Roles and Port States	328
50	Figure 13-4—A Backup Port.....	329
51	Figure 13-5—“Ring Backbone” example.....	329
52	Figure 13-6—An MST Bridge network.....	331
53	Figure 13-7—CIST Priority Vectors, Port Roles, and MST Regions	332
54		

1	Figure 13-8—MSTI Active Topology in Region 2	333
2	Figure 13-9—CIST and MSTI active topologies in Region 1 of the example network	344
3	Figure 13-10—Agreements and Proposals	347
4	Figure 13-11—CIST and MSTI Active Topologies in Region 2 of Figure 13-6—	348
5	Figure 13-12—Enhanced Agreements.....	350
6	Figure 13-13—Spanning tree protocol state machines—overview and relationships.....	357
7	Figure 13-14—MSTP overview notation	358
8	Figure 13-15—Port Timers state machine.....	382
9	Figure 13-16—Port Receive state machine	382
10	Figure 13-17—Port Protocol Migration state machine.....	383
11	Figure 13-18—Bridge Detection state machine	383
12	Figure 13-19—Port Transmit state machine.....	384
13	Figure 13-20—Port Information state machine	385
14	Figure 13-21—Port Role Selection state machine.....	386
15	Figure 13-22—Disabled Port role transitions	387
16	Figure 13-23—Port Role Transitions state machine—MasterPort.....	387
17	Figure 13-24—Port Role Transitions state machine—RootPort	388
18	Figure 13-25—Port Role Transitions state machine—DesignatedPort.....	389
19	Figure 13-26—Port Role Transitions state machine—AlternatePort and BackupPort	389
20	Figure 13-27—Port State Transition state machine.....	390
21	Figure 13-28—Topology Change state machine	391
22	Figure 13-29—L2 Gateway Port Receive state machine.....	392
23	Figure 14-1—MST BPDU parameters and format.....	397
24	Figure 14-2—MSTI Configuration Message parameters and format.....	401
25	Figure 15-1—Internal organization of the MAC sublayer in a Provider Bridged Network.....	402
26	Figure 15-2—Port-based service interface to a Provider Bridged Network.....	403
27	Figure 15-3—Port-based service interface to a Provider Bridged Network.....	404
28	Figure 15-4—C-tagged service interface to a Provider Bridged Network	404
29	Figure 15-5—C-tagged service interface to a Provider Bridged Network	404
30	Figure 15-6—Customer Edge Ports.....	405
31	Figure 15-7—S-tagged service interface to a Provider Bridged Network.....	405
32	Figure 15-8—S-tagged interface to a Provider Bridged Network	406
33	Figure 16-1—Provider Bridged Network with interface examples.....	410
34	Figure 17-1—C-VLAN component internal LAN managed system	457
35	Figure 17-2—I/B-component internal LAN managed system	462
36	Figure 18-1—One Maintenance Domain: operator’s view	850
37	Figure 18-2—One service instance: operator’s view.....	851
38	Figure 18-3—One service instance: customer’s view	851
39	Figure 18-4—MEP and MIP Symbols.....	852
40	Figure 18-5—Maintenance Associations: one service instance in a provider network.....	853
41	Figure 18-6—Maintenance Associations: Expansion of Figure 18-5	854
42	Figure 18-7—MEPs, MIPs, and MD Levels	855
43	Figure 19-1—CFM Protocol shims	856
44	Figure 19-2—Maintenance association End Point (MEP)	859
45	Figure 19-3—MIP Half Function	864
46	Figure 19-4—Linktrace Output Multiplexer shim.....	866
47	Figure 19-5—Linktrace Output Multiplexer architecture	867
48	Figure 20-1—MEP state machines—overview and relationships	879
49	Figure 20-2—MEP Continuity Check Initiator state machine	886
50	Figure 20-3—MHF Continuity Check Receiver state machine.....	888
51	Figure 20-4—MEP Continuity Check Receiver state machine	891
52	Figure 20-5—Remote MEP state machine	893
53	Figure 20-6—Remote MEP Error state machine.....	894
54	Figure 20-7—MEP Cross Connect state machine	895

1	Figure 20-8—MEP Traffic Field Mismatch state machine	897
2	Figure 20-9—MEP Local Mismatch state machine	897
3	Figure 20-10—MP Loopback Responder state machine	899
4	Figure 20-11—MEP Loopback Initiator transmit state machine.....	901
5	Figure 20-12—MEP Loopback Initiator receive state machine	902
6	Figure 20-13—MEP Fault Notification Generator state machine	905
7	Figure 20-13—MEP Fault Notification Generator state machine	906
8	Figure 20-14—MEP Linktrace Initiator receive state machine	911
9	Figure 20-15—Linktrace Responder, MEPs, MHFs, and LOMs	912
10	Figure 20-16—LTM Receiver state machine	918
11	Figure 20-17—LTR Transmitter state machine.....	918
12	Figure 22-1—MEPs and MIPs distinguished by VID (incomplete picture)	948
13	Figure 22-2—Alternate view of Forwarding process	949
14	Figure 22-3—Combining per-VLAN Maintenance Points into two shims.....	950
15	Figure 22-4—More complete picture of Maintenance Point placement in a Bridge Port.....	951
16	Figure 22-5—Service instance spanning two Bridges protected by Up MPs.....	953
17	Figure 22-6—Service instance spanning two Bridges protected by Down MPs.....	953
18	Figure 22-7—Maintenance Point placement in a non-VLAN aware Bridge Port.....	955
19	Figure 22-8—Maintenance Point placement relative to other standards.....	956
20	Figure 22-9—Creating MEPs and MIPs.....	959
21	Figure 22-10—CFM in a Provider Edge Bridge C-tagged service interface.....	965
22	Figure 22-11—Up MEPs in a Management Port.....	966
23	Figure 22-12—CFM in the enterprise environment	967
24	Figure 22-13—CFM on a Bridge conformant to IEEE Std 802.1Q-2005	968
25	Figure 23-1—TPMR connecting two Bridge Ports	969
26	Figure 23-2—TPMR chain connecting Bridge Ports	969
27	Figure 23-3—MAC Status Shims and the MAC Status Propagation Entity	971
28	Figure 23-4—Adding connectivity.....	973
29	Figure 23-5—Losing connectivity.....	974
30	Figure 23-6—TPMR recovery.....	975
31	Figure 23-7—Notification from one end of the link to the other	976
32	Figure 23-8—Immediate MAC status notification at the end of a link	976
33	Figure 23-9—MSPE state machine overview	977
34	Figure 23-10—Status Transition state machine.....	981
35	Figure 23-11—Status Notification state machine.....	982
36	Figure 23-12—MSPDU structure.....	984
37	Figure 25-1—Internal organization of the MAC sublayer in a PBBN	987
38	Figure 25-2—Provider Backbone Bridge terminology	988
39	Figure 25-3—Customer service interface types	989
40	Figure 25-4—Port-based service interface	990
41	Figure 25-5—Port-based interface equipment.....	991
42	Figure 25-6—Encapsulated service frames at ISS	992
43	Figure 25-7—S-tagged service interface	993
44	Figure 25-8—S-tagged service interface equipment	993
45	Figure 25-9—I-tagged service interface	995
46	Figure 25-10—I-tagged service interface equipment	995
47	Figure 25-11—S-tagged and Port-based service interface access classifications	998
48	Figure 25-12—I-tagged service interface access protection classifications	999
49	Figure 25-13—Internal organization of the MAC sublayer in a PBB-TE Region	1001
50	Figure 25-14—PBB-TE Region	1003
51	Figure 25-15—Transparent service interface	1005
52	Figure 25-16—Transparent service interface equipment	1005
53	Figure 26-1—PBBN example.....	1008
54	Figure 26-2—CFM Shim Model	1015

1	Figure 26-3—CFM example applied to a Port-based and S-tagged Service Interface.....	1017
2	Figure 26-4—CFM example applied to an I-tagged Service Interface.....	1018
3	Figure 26-5—CFM example applied to a hierarchal E-NNI, CBP-PIP Demarc.....	1020
4	Figure 26-6—CFM example applied to a peer E-NNI, CBP-PIP.....	1021
5	Figure 26-7—Independent ESPs using the same ESP-DAs and ESP-VIDs	1023
6	Figure 26-8—PBB-TE MEP placement in a CBP.....	1024
7	Figure 26-9—Protection Switching Architecture	1026
8	Figure 26-10—PBB-TE point-to-point protection switching.....	1028
9	Figure 26-11—Mapping data traffic to the protection entity	1030
10	Figure 26-12—Relationships of the Protection switching state machines—overview	1030
11	Figure 26-13—Hold-off state machine.....	1034
12	Figure 26-14—Clear Manual Switch state machine.....	1034
13	Figure 26-15—Service Mapping state machine	1035
14	Figure 29-1—Forward path test (FPT)	1040
15	Figure 29-2—Return path test	1041
16	Figure 29-3—Combination of forward path test and return path test.....	1042
17	Figure 29-4—Detailed Functions of Reflection Responder	1043
18	Figure 29-5—RFM Receiver on a non-MP.....	1046
19	Figure 29-6—Return Path Decapsulator Responder	1047
20	Figure 29-7—RR Filter state machine.....	1052
21	Figure 29-8—RR Encapsulation state machine.....	1053
22	Figure 29-9—RR Transmit state machine.....	1053
23	Figure 29-10—RFM Receiver state machine	1055
24	Figure 29-11—Decapsulator Responder state machine.....	1057
25	Figure 30-1—Congestion detection in QCN CP	1063
26	Figure 30-2—Sampling (reflection) probability in QCN CP as a function of Fb	1064
27	Figure 30-3—QCN RP operation	1064
28	Figure 30-4—Byte Counter and Timer interaction with Rate Limiter	1066
29	Figure 30-5—CP-RP peering in VLAN Bridged Network.....	1069
30	Figure 30-6—CP-RP peering in Provider Backbone Bridged Network	1069
31	Figure 31-1—Congestion Points and congestion aware queues in a bridge.....	1071
32	Figure 31-2—Congestion aware queue functions in an end station	1072
33	Figure 31-3—Per-CNPV station function	1074
34	Figure 32-1—Congestion Notification Domain defense state machine	1087
35	Figure 32-2—RP rate control state machine.....	1099
36	Figure 32-3—CP-RP peering in any hierarchical Bridged Network	1100
37	Figure 34-1—Queuing model for a Talker station	1112
38	Figure 35-1—Operation of MSRP.....	1115
39	Figure 35-2—Format of the components of the reservation FirstValue fields.....	1125
40	Figure 35-3—Format of the components of the Domain FirstValue.....	1131
41	Figure C-1—CSN Backbone	1208
42	Figure C-2—Bridge’s CSN Model for Bandwidth Reservation.....	1209
43	Figure C-3—Talker MSRPDU flow	1210
44	Figure C-4—Listener MSRPDU flow	1210
45	Figure C-5—IEEE DMN Device Attribute IE	1212
46	Figure C-6—DMN ConfirmationTransaction	1214
47	Figure C-7—Bandwidth Reservation - Bridge Model for IEEE 802.11 BSS (STA Downstream Port) ...	1217
48	Figure C-8—Bandwidth Reservation - Bridge Model for IEEE 802.11 BSS (STA Upstream Port).....	1217
49	Figure C-9—Bandwidth Reservation - Bridge Model for IEEE 802.11 BSS (Direct Link Setup).....	1218
50	Figure C-10—MSRP/802.11 Query Flows	1218
51	Figure C-11—MSRP/802.11 Talker STA to Listener STA Reservation Flows.....	1219
52	Figure C-12—MSRP/802.11 “Bridged” Listener to Talker STA Reservation Flows.....	1220
53	Figure C-13—MSRP/802.11 Listener STA to “Bridged” Talker Reservation Flows.....	1220
54	Figure D-1—Port VLAN ID TLV Format	1226

1	Figure D-2—Port And Protocol VLAN ID TLV Format	1226
2	Figure D-3—VLAN Name TLV format.....	1227
3	Figure D-4—Protocol Identity TLV format	1228
4	Figure D-5—VID Usage Digest TLV format	1229
5	Figure D-6—Management VID TLV format	1229
6	Figure D-7—Link Aggregation TLV format.....	1230
7	Figure D-8—Congestion Notification TLV format.....	1231
8	Figure F-1—Connecting independent VLANs—1	1273
9	Figure F-2—Connecting independent VLANs—2	1274
10	Figure F-3—Duplicate MAC Addresses	1274
11	Figure F-4—Asymmetric VID use: “multi-netted server”	1275
12	Figure F-5—Asymmetric VLAN use: “Rooted-Multipoint”	1277
13	Figure G-1—Example of IEEE 802.3 MAC frame format	1281
14	Figure H-1—Static filtering inconsistency	1285
15	Figure H-2—Interoperability with IEEE 802.1D Bridges: example 1	1286
16	Figure H-3—Interoperability with IEEE 802.1D Bridges: example 2	1287
17	Figure H-4—Interoperability between Port-based and Port-and-Protocol-based classification.....	1289
18	Figure J-1—Up MPs in a CFM Port	1304
19	Figure K-1—TPMR as UNI demarcation device	1307
20	Figure K-2—TPMRs with aggregated links	1308
21	Figure K-3—Multiple TPMRs.....	1308
22	Figure K-4—Recovery at the end of a chain	1309
23	Figure K-5—Near simultaneous recoveries	1310
24	Figure K-6—Near simultaneous failure and recovery.....	1310
25	Figure K-7—Loss with quick recovery	1311
26	Figure L-1—Credit-based shaper operation—no conflicting traffic	1314
27	Figure L-2—Credit-based shaper operation—conflicting traffic	1315
28	Figure L-3—Credit-based shaper operation—burst traffic.....	1316
29	Figure L-4—Interference and latency.....	1320
30	Figure L-5—Burst behavior and credit.....	1320
31	Figure L-6—Fan-in scenario	1324
32	Figure L-7—Permanent delay scenario	1325
33	Figure L-8—Building up buffer occupancy—1	1325
34	Figure L-9—Building up buffer occupancy—2	1326
35	Figure L-10—Building up buffer occupancy—3	1326
36	Figure L-11—Building up buffer occupancy—4	1326
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		

Tables

1		
2		
3	Table 6-1—Priority to MAC service class mapping	65
4	Table 6-2—MAC service class to priority mapping.....	65
5	Table 6-3—Priority Code Point encoding	71
6	Table 6-4—Priority Code Point decoding	71
7	Table 6-5—Priority regeneration.....	72
8	Table 6-6—Default SRP domain boundary port priority regeneration override values.....	73
9	Table 6-7—Service Access Priority	85
10	Table 6-8—Encapsulated Addresses EtherType	92
11	Table 8-1—C-VLAN component Reserved addresses	116
12	Table 8-2—S-VLAN component Reserved addresses	117
13	Table 8-3—TPMR component Reserved addresses	117
14	Table 8-4—Recommended priority to traffic class mappings.....	119
15	Table 8-5—Transmission selection algorithm identifiers	120
16	Table 8-6—Ageing time parameter value	127
17	Table 8-8—Combining Static Filtering Entry and MAC Address Registration Entry for	
18	“All Group Addresses” and “All Unregistered Group Addresses”	134
19	Table 8-7—Combining Static and Dynamic Filtering Entries for an individual MAC Address	134
20	Table 8-9—Forwarding or Filtering for specific group MAC Addresses	135
21	Table 8-11—Determination of whether a Port is in a VID’s member set	136
22	Table 8-10—Forwarding or Filtering with Dynamic Reservation Entries	136
23	Table 8-12—Standard LLC address assignment	140
24	Table 8-13—Continuity Check Message Group Destination MAC Addresses	147
25	Table 8-14—Linktrace Message Group Destination MAC Addresses.....	147
26	Table 9-1—IEEE 802.1Q EtherType allocations	150
27	Table 9-2—Reserved VID values.....	150
28	Table 9-3—Reserved I-SID values.....	152
29	Table 10-1—MRP application addresses	160
30	Table 10-2—MRP EtherType values	161
31	Table 10-3—Applicant state table	174
32	Table 10-4—Registrar state table	175
33	Table 10-5—LeaveAll state table.....	176
34	Table 10-6—PeriodicTransmission state table	176
35	Table 10-7—MRP timer parameter values	177
36	Table 12-1—Bandwidth Availability Parameter Table row elements.....	312
37	Table 12-2—Transmission Selection Algorithm Table row elements	312
38	Table 12-3—Priority Regeneration Override Table row elements.....	313
39	Table 12-4—CN component managed object row elements	314
40	Table 12-5—CN component priority managed object row elements	315
41	Table 12-7—Congestion Point managed object row elements.....	316
42	Table 12-6—CN Port priority managed object row elements	316
43	Table 12-8—Reaction Point port priority managed object row elements	317
44	Table 12-9—Reaction Point group managed object row elements	318
45	Table 12-12—SRP Latency Parameter Table row elements	319
46	Table 12-10—SRP Bridge Base Table row elements.....	319
47	Table 12-11—SRP Bridge Port Table row elements.....	319
48	Table 12-13—SRP Stream Table row elements	320
49	Table 12-14—SRP Reservations Table row elements.....	321
50	Table 13-1—Configuration Digest Signature Key	336
51	Table 13-2—Sample Configuration Digest Signature Keys.....	337
52	Table 13-3—Bridge and Port Priority values	350
53	Table 13-4—Port Path Cost values.....	351
54		

1	Table 13-5—Timer and related parameter values	359
2	Table 17-1—Structure of the MIB modules.....	414
3	Table 17-2—IEEE8021-TC MIB Structure	415
4	Table 17-3—IEEE8021-BRIDGE MIB structure and	
5	relationship to IETF RFC 4188 and this standard	417
6	Table 17-4—IEEE 802.1D objects not in the IEEE8021-BRIDGE MIB	421
7	Table 17-5—IEEE8021-SPANNING-TREE MIB structure and relationship to	
8	IETF RFC 4318 and this standard	421
9	Table 17-6—Clause 12 objects not in the IEEE8021-SPANNING-TREE MIB	423
10	Table 17-7—IEEE8021-QBRIDGE MIB structure and	
11	relationship to IETF RFC 4363 and this standard	424
12	Table 17-8—Clause 12 management not in IEEE8021-Q-BRIDGE MIB	429
13	Table 17-9—IEEE8021-PB MIB structure and relationship to this standard	430
14	Table 17-10—IEEE8021-MSTP MIB structure and relationship to this standard.....	432
15	Table 17-11—IEEE8021-CFM MIB correspondence between variables, managed objects,	
16	and MIB objects.....	435
17	Table 17-12—IEEE8021-CFM-V2 correspondence between variables, managed objects,	
18	and MIB objects.....	439
19	Table 17-13—IEEE8021-PBB MIB structure and relationship to this standard	441
20	Table 17-14—IEEE8021-DDCFM MIB structure and relationship	
21	to this standard	444
22	Table 17-15—IEEE8021-PBBTE MIB Structure and relationship to this standard	446
23	Table 17-16—Example of ieee8021PbbTeTeSidTable	447
24	Table 17-17—IEEE8021-TPMR MIB Structure and relationship to this standard	448
25	Table 17-18—FQSS MIB structure and object cross reference.....	450
26	Table 17-19—Variables, managed object tables, and MIB objects.....	451
27	Table 17-20—SRP MIB structure and object cross reference.....	453
28	Table 17-21—PBB-TE required MIB compliances	463
29	Table 17-22—Sensitive managed objects: tables and notifications	469
30	Table 17-23—Sensitive managed objects: variables in dot1agCfmMdTable	470
31	Table 17-24—Sensitive managed objects (of DDCFM): tables and notifications	471
32	Table 17-25—Sensitive managed objects (of DDCFM) for read.....	471
33	Table 17-26—Provider Bridge service interface parameters	485
34	Table 17-27—Provider Backbone Bridge service interface parameters	489
35	Table 19-1—Actions taken by MP OpCode Demultiplexers	861
36	Table 19-2—SAP use for Linktrace Messages and Linktrace Replies.....	868
37	Table 20-1—Fault Alarm defects and priorities	873
38	Table 20-2—Deriving enableRmepDefect and Port Status TLV in a Bridge	883
39	Table 21-1—CFM PDU Encapsulation: Length/Type Media	925
40	Table 21-2—CFM PDU Encapsulation: LLC Media	925
41	Table 21-3—Common CFM Header format	926
42	Table 21-5—TLV format.....	927
43	Table 21-4—OpCode Field range assignments	927
44	Table 21-7—Organization-Specific TLV format	928
45	Table 21-6—Type Field values	928
46	Table 21-8—Sender ID TLV format	929
47	Table 21-11—Interface Status TLV format.....	931
48	Table 21-12— Interface Status TLV values	931
49	Table 21-9—Port Status TLV format	931
50	Table 21-10—Port Status TLV values.....	931
51	Table 21-13—Data TLV format	932
52	Table 21-14—End TLV format	932
53	Table 21-15—Continuity Check Message format	933
54	Table 21-16—CCM Interval field encoding.....	934

1	Table 21-19—Maintenance Domain Name Format	935
2	Table 21-17—CCM MAID field format: Maintenance Domain present	935
3	Table 21-18—CCM MAID field format: Maintenance Domain not present	935
4	Table 21-20—Short MA Name Format	936
5	Table 21-21—Loopback Message and Loopback Reply formats.....	937
6	Table 21-22—PBB-TE MIP TLV format.....	938
7	Table 21-23—Linktrace Message format	939
8	Table 21-24—Linktrace Message Flags field.....	940
9	Table 21-25—LTM Egress Identifier TLV format.....	941
10	Table 21-26—Linktrace Reply format	942
11	Table 21-27—Linktrace Reply Flags field	942
12	Table 21-29—LTR Egress Identifier TLV format	943
13	Table 21-28—Relay Action field values	943
14	Table 21-30—Reply Ingress TLV format	944
15	Table 21-31—Ingress Action field values	944
16	Table 21-32—Reply Egress TLV format	945
17	Table 21-33—Egress Action field values.....	946
18	Table 22-1—MEP creation	959
19	Table 22-2—MIP creation	960
20	Table 22-3—Bandwidth required for CCMs for 1 MA	963
21	Table 22-4—Bandwidth required for CCMs for 1000 MAs	963
22	Table 23-1—Time sequence diagram symbols	973
23	Table 23-2—MSP performance parameters	979
24	Table 23-3—MSP EtherType assignment	984
25	Table 23-4—MSP Packet Types.....	985
26	Table 26-1—Backbone Service Instance Group address OUI	1010
27	Table 26-8—Protection Requests Hierarchy	1032
28	Table 29-1—RFM format.....	1058
29	Table 29-2—SFM format	1059
30	Table 32-1—LLDP instance selection managed object overrides.....	1080
31	Table 32-2—CND defense mode selection managed object overrides	1080
32	Table 32-3—Determining cnpdIsAdminDefMode and cnpdDefenseMode.....	1086
33	Table 32-4—Correspondence of QCN protocol and CCF message fields	1088
34	Table 32-5—NewCpSampleBase() return value as a function of cpFb	1091
35	Table 33-3—Congestion Notification Message Encapsulation: Length/Type Media.....	1103
36	Table 33-1—Congestion Notification Tag Encapsulation: Length/Type Media.....	1103
37	Table 33-2—Congestion Notification Tag Encapsulation: LLC Media.....	1103
38	Table 33-5—Congestion Notification Message PDU	1104
39	Table 33-4—Congestion Notification Message Encapsulation: LLC Media	1104
40	Table 34-1—Recommended priority to traffic class mappings for SR classes A and B.....	1111
41	Table 34-2—Recommended priority to traffic class mappings for SR class B only.....	1111
42	Table 35-1—AttributeType Values	1121
43	Table 35-2—AttributeLength Values	1122
44	Table 35-3—FourPackedEvent Values	1123
45	Table 35-4—MSRP FirstValue NumberOfValues example	1124
46	Table 35-5—TSpec Components Examples.....	1127
47	Table 35-6—Reservation Failure Codes.....	1129
48	Table 35-7—SR class ID	1131
49	Table 35-8—Summary of Talker primitives	1133
50	Table 35-9—Summary of Listener primitives.....	1133
51	Table 35-10—Talker Attribute Propagation per port	1137
52	Table 35-11—Incoming Listener Attribute Propagation per port	1138
53	Table 35-12—Updating Dynamic Reservation Entries	1139
54	Table 35-13—Updating <i>operIdleSlope(N)</i>	1139

1	Table 35-14—Listener Declaration Type Summation.....	1140
2	Table C-1—SRP to MoCA PQoS Transaction mapping.....	1216
3	Table C-2—SRP TSpec to MoCA TSPEC mapping.....	1216
4	Table C-3—SRP StreamID to MoCA PQoS Flow transaction mapping	1216
5	Table C-4—SRP to MLME QoS Services mapping	1222
6	Table C-5—EDCA-AC for AV Streams	1223
7	Table C-6—HCCA for AV Streams	1224
8	Table D-1— IEEE 802.1 Organizationally Specific TLVs	1225
9	Table D-2—Port and protocol capability/status	1226
10	Table D-3—Link aggregation capability/status.....	1230
11	Table D-4—IEEE 802.1 extension MIB object group conformance requirements.....	1233
12	Table D-5—IEEE 802.1/LLDP extension MIB object cross reference.....	1234
13	Table E-6—State machine symbols.....	1271
14	Table I-1—Traffic type to traffic class mapping	1293
15	Table I-2—Traffic type acronyms	1294
16	Table I-3—Defining traffic types	1295
17	Table I-4—Defining traffic types — Credit-based shaper support of one SR class.....	1296
18	Table I-5—Defining traffic types — Credit-based shaper support of two SR classes	1296
19	Table I-6—Priority Code Point encoding.....	1298
20	Table I-7—Priority Code Point decoding.....	1298
21	Table J-1—Provider MD Level allocation	1300
22	Table J-2—IEEE / ITU-T terminology differences.....	1300
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54

IEEE Standard for Local and metropolitan area networks—

Media Access Control (MAC) Bridges and Virtual Bridged Local Area Networks

1. Overview

IEEE 802[®] Local Area Networks (LANs)¹ of all types can be connected together with Media Access Control (MAC) Bridges, as specified in IEEE Std 802.1D[™].^{2,3} This standard defines the operation of Bridges that permit the definition, operation, and administration of Virtual LANs (VLANs) within Virtual Bridged Local Area Networks.

This standard further extends the specification of VLAN-aware MAC Bridges to enable a service provider organization to use a common infrastructure of Bridges and LANs to offer the equivalent of separate LANs, Bridged, or Virtual Bridged Local Area Networks to independent customer organizations.

This standard specifies protocols and protocol entities within the architecture of VLAN-aware Bridges that provide capabilities for detecting, verifying, and isolating connectivity failures in Virtual Bridged Local Area Networks. These capabilities can be used in networks operated by multiple independent organizations, each with restricted management access to each other's equipment.

The data driven and data dependent connectivity fault management capabilities include tools to facilitate diagnosis and isolation of faults sensitive to, or caused by, particular data patterns in transmitted frames.

This standard specifies protocols, procedures, and managed objects that support congestion management of long-lived data flows within network domains with a bandwidth-delay product on the order of 5 Mbits or less. Such flows are typically encountered in data centers, backplane fabrics, computing clusters, and storage networks. This is achieved by enabling bridges to signal congestion to end stations capable of transmission rate limiting to avoid frame loss. This mechanism enables support for higher layer protocols that are highly loss or latency sensitive. VLAN tag encoded priority values are allocated to segregate frames subject to congestion control, allowing simultaneous support of both congestion controlled and other higher layer protocols. This standard does not specify communication or reception of congestion notification information to or from end stations outside the congestion controlled domain or encapsulation of frames from those end stations across the domain.

¹IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

²Information on references can be found in Clause 2.

³Throughout this standard, references to IEEE Std 802.1D, without qualification as to the date of publication, refer to the most recent revision or edition of the standard that is identified in the references section (Clause 2). In those cases where the reference is intended to be to an earlier published version of the standard, the reference is qualified by the publication date of that revision or edition.

1 This standard specifies protocols, procedures and managed objects, usable by existing higher layer
2 mechanisms, that allow network resources to be reserved for specific traffic streams traversing a bridged
3 local area network. It characterizes resource requirements of traffic streams to a level sufficient for bridges
4 to determine the required resources and provides a mechanism for dynamic maintenance of those resources.
5

6 7 **1.1 Scope**

8
9 This standard specifies Media Access Control (MAC) Bridges that interconnect individual Local Area
10 Networks (LANs), each supporting the IEEE 802 MAC service using a different or identical media access
11 control method, to provide Bridged Local Area Networks and Virtual LANs (VLANs).
12

13 14 **1.2 Purpose**

15
16 MAC Bridges, as specified by this standard, allow the compatible interconnection of information technology
17 equipment attached to separate individual LANs.
18

19 20 **1.3 Introduction**

21 For the purpose of compatible interconnection of information technology equipment using the IEEE 802
22 MAC Service supported by interconnected IEEE 802 standard LANs using different or identical media
23 access control methods, this standard specifies the operation of MAC Bridges that support Virtual LANs
24 (VLANs). To this end it
25

- 26
- 27 a) Positions the support of VLANs within an architectural description of the MAC Sublayer;
 - 28 b) Defines the principles of operation of the VLAN-aware Bridge in terms of the support and
29 preservation of the MAC Service, and the maintenance of Quality of Service;
 - 30 c) Specifies an Enhanced Internal Sublayer Service provided to the Media Access Independent
31 functions that provide frame relay in a VLAN-aware Bridge;
 - 32 d) Establishes the principles and a model of Virtual Bridged Local Area Network operation;
 - 33 e) Identifies the functions to be performed by VLAN-aware Bridges, and provides an architectural
34 model of the operation of a Bridge in terms of Processes and Entities that provide those functions;
 - 35 f) Specifies a frame format that allows a VLAN Identifier (VID) and priority information to be carried
36 by VLAN tagged user data frames;
 - 37 g) Specifies the rules that govern the addition or removal of VLAN tags to and from user data frames;
 - 38 h) Specifies the rules that govern the ability to carry user data in either Canonical format or Non-
39 canonical format in VLAN-tagged frames;
- 40

41 NOTE 1—The meanings of the terms *Canonical format* and *Non-canonical format* are discussed in IEEE Std 802.⁴
42

- 43 i) Establishes the requirements for automatic configuration of VLAN topology;
 - 44 j) Establishes the requirements for VLAN-aware Bridge Management in a Virtual Bridged Local Area
45 Network, identifying managed objects and defining management operations;
 - 46 k) Defines SMIV2 (IETF STD 58) MIB modules for the management of VLAN-aware Bridge
47 capabilities including Spanning Tree Protocols and Provider Bridges.
 - 48 l) Defines the operation of the Multiple Spanning Tree algorithm and protocol (MSTP);
 - 49 m) Describes the protocols and procedures necessary to support interoperation between MST and SST
50 Bridges in the same Virtual Bridged Local Area Networks;
 - 51 n) Specifies the requirements to be satisfied by equipment claiming conformance to this standard.
52
- 53

54 ⁴Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.