



Photography—Electronic still-picture imaging—Noise measurements



This Australian Standard® was prepared by Committee MS-065, Photography. It was approved on behalf of the Council of Standards Australia on 20 April 2015. This Standard was published on 12 May 2015.

The following are represented on Committee MS-065:

- Australian Chamber of Commerce and Industry
 - Australian Industry Group
 - Australian Institute of Professional Photographers
 - CHOICE
 - National ICT Australia
 - State Library of New South Wales
 - University of New South Wales
 - University of Technology, Sydney
 - University of Western Sydney
-

This Standard was issued in draft form for comment as DR AS ISO 15739:2015.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

**Photography—Electronic still-picture
imaging—Noise measurements**

First published as AS ISO 15739:2015.

COPYRIGHT

© Standards Australia Limited

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968.

Published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 978 1 76035 050 5

PREFACE

This Standard was prepared by the Standards Australia Committee MS-065, Photography.

The objective of this Standard is to specify methods for measuring and reporting the noise versus signal level and dynamic range of digital still cameras. It applies to both monochrome and colour electronic digital still cameras.

This Standard is identical with, and has been reproduced from, ISO 15739:2013, *Photography—Electronic still-picture imaging—Noise measurements*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) In the source text ‘this International Standard’ should read ‘this Australian Standard’.
- (b) A full point substitutes for a comma when referring to a decimal marker.

None of the normative references in the source document have been adopted as Australian or Australian/New Zealand Standards.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the annex to which they apply. A ‘normative’ annex is an integral part of a Standard, whereas an ‘informative’ annex is only for information and guidance.

CONTENTS

1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Test conditions	3
4.1	General	3
4.2	Illumination	3
4.3	Temperature and relative humidity	4
4.4	White balance	4
4.5	Infrared (IR) blocking filter	4
4.6	Photosite integration time	4
4.7	Colour noise weighting	4
4.8	Compression	5
5	Noise measurement procedures	5
5.1	General	5
5.2	Measurement of a DSC having a removable lens	6
5.3	Measurement of a DSC having manual exposure control	7
5.4	Measurement of a DSC using a test chart	7
6	Calculation and reporting of results	9
6.1	General	9
6.2	Signal-to-noise ratios — large area	9
6.3	DSC dynamic range	12
	Annex A (normative) Noise component analysis	14
	Annex B (normative) Visual noise measurements	18
	Annex C (informative) Removing low frequency variations from the image data	27
	Annex D (informative) Recommended procedure for determining signal to noise ratio	29
	Annex E (informative) Recommended practical viewing conditions for various output media	30
	Bibliography	31

INTRODUCTION

Noise is an important attribute of electronic photographic systems. The camera noise measurements described in this International Standard are performed in the digital domain, using digital analysis techniques. Since the noise performance of an image sensor may vary significantly with exposure time and operating temperature, these operating conditions are specified. The visibility of noise to human observers depends on the magnitude of the noise, the apparent tone of the area containing the noise and the spatial frequency of the noise. The magnitude of the noise present in an output representation depends on the noise present in the stored image data and the contrast amplification or gain applied to the data in producing the output. The noise visibility is different for the luminance (or monochrome) channel and the colour (or colour difference) channels. Therefore, this International Standard accounts for these factors in measuring and reporting the camera noise measurements. [Annex A](#) specifies the method for determining the components of the digital camera noise from a number of samples. The perceptibility of noise in an image can vary depending on the viewing distance, spatial frequency, density, colour and viewing conditions. [Annex B](#) describes a procedure for measuring the visual noise level using a human visual model as a method for weighting the spectral components of the noise. A method for removing low frequency variations in the patch data resulting, for example, from luminance shading is given in [Annex C](#). A recommended step-by-step procedure for determining the signal to noise ratio and incremental gain is provided in [Annex D](#). In [Annex E](#) recommendations for practical viewing conditions for various output media are given.

AUSTRALIAN STANDARD

Photography—Electronic still-picture imaging—Noise measurements**1 Scope**

This International Standard specifies methods for measuring and reporting the noise versus signal level and dynamic range of digital still cameras. It applies to both monochrome and colour electronic digital still cameras.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7589:2002, *Photography — Illuminants for sensitometry — Specifications for daylight, incandescent tungsten and printer*

ISO 12232:2006, *Photography — Digital still cameras — Determination of exposure index, ISO speed ratings, standard output sensitivity, and recommended exposure index*

ISO 14524:2009, *Photography — Electronic still-picture cameras — Methods for measuring opto-electronic conversion functions (OECFs)*

ITU-R BT.709-5, *Parameter values for the HDTV Standards for production and International programme exchange*

CIE 15:2004, *Colorimetry*, 3rd edition

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1**camera opto-electronic conversion function****camera OECF**

relationship between the input scene log luminances and the pixel values for an opto-electronic digital capture system

Note 1 to entry: The units of measurement for this function are \log_{10} candelas per square metre.

3.2**clipping value**

pixel value that remains constant for further increases in exposure (highlight clipping value) or for further decreases in exposure (dark clipping value)

3.3**digital still camera****DSC**

camera that produces a digital still image from the digitized output of a solid-state photo sensor and records the digital still image using a digital memory, such as a removable memory card